



BNC Input LCD Monitors

- ~ Video Inputs: (2) BNC (1) VGA (1) S-Video
- ~ Video Outputs: (1) BNC (2) Audio RCA (1) Stereo 3.5mm
- ~ Picture-In-Picture allows multi-picture display
- ~ Built-in 2D Comb Filter and 3D De-interlace

Specifications	MON-LCD-BNC15	MON-LCD-BNC17	MON-LCD-BNC19
Recommended Resolution	4:3 XGA (1024 x 768)	5:4 SXGA(1280x1024)	
Video Inputs / Video Outputs	Video input (BNC) x2, Video Loop output (BNC) x1, S-video, VGA		
PC Input	15 pin D-Sub (Analog RGB) for VGA Input		
Audio Input & Output	RCA jack (L/R)x2, Stereo 3.5 mm Input x1		
Viewing Angle (U/D/L/R)	75/60/75/75	80/80/80/80	
Power Consumption	Approx. 17 Watts	Approx. 15 Watts	Approx. 25 Watts
Pixel Pitch	0.297mm	0.264mm	0.294 mm
Display Colors	16.2 Million Colors	16.7 Million Colors	
Contrast Ratio	480:1 Typical	1000:1 Typical	
Luminance, White	300cd/m ² Typical		400cd/m ² Typical
Response Time	8ms Typical	5ms Typical	
Image Processor	8 Bit; 3-6CH Processor		
Signal Timing	LVDS		
Operating Temperature	0°C - 50°C		
Operating Relative Humidity	0 ~ 90% RH		
Power Supply	DC 12V Adapter Supplied, AC 100V~240V		
Screen Control Language	English / French / Spanish / Dutch / Italian / Chinese		
Radiation Standard	TCO 99		
Wall Mount	VESA		
Unit N.W./ G. W. (Approx.)	3.5KG / 4.5KG	4.5KG / 5.5KG	7KG / 8KG
Gift Box Size(LxWxD mm)	375 x 146 x 390	430 x 145 x 375	490 x 185 x 490