

CCTV Camera Pros

22" LCD BNC Monitors for CCTV



Plastic Case

- ✧ Video input BNC x 2 / VGA x 1 / S-Video x 1
- ✧ Video Loop output BNC x 1 / Audio RCA x 2 / Stereo 3.5mm input x1
- ✧ Picture-In-Picture feature that allows multi-picture display
- ✧ **Built-in 2D Comb filter, 3D De-interlace**

Specification for model MON-LCD-22BNC

Recommended Resolution	16:10 WXGA (1680 x 1050)
Video Inputs / Video Outputs	Video input (BNC) x2, Video Loop output (BNC) x1, S-video, VGA
PC Input	15 pin D-Sub (Analog RGB) for VGA Input
Audio Input & Output	RCA jack (L/R)x2, Stereo 3.5 mm Input x1
Viewing Angle (U/D/L/R)	80/80/80/80
Image Processor	8 Bit; 3-6CH Processor
Power Consumption	Approx. 25 Watts
Pixel Pitch	0.282mm
Display Colors	16.2 Million Colors
Contrast Ratio	1000:1 Typical
Luminance, White	300cd/m ² Typical
Response Time	5ms Typical
Signal Timing	LVDS
Operating Temperature	0°C - 50 °C
Operating Relative Humidity	0 ~ 90% RH
Power Supply	DC 12V Adapter Supplied, AC 100V~240V
Screen Control Language	English / French / Spanish / Dutch / Italian / Chinese
Radiation Standard	TCO 99
Wall Mount	VESA
Unit N.W./ G. W.	Approx. 7.5KG/8.5KG
Gift Box Size(LxWxD mm)	570x160x470