



SPECIFICATIONS

Model Number	IP-V72PT	IP-V72PT-P	IP-V72PTW	IP-V72PTW-P
TV System	NTSC	PAL	NTSC	PAL
Image Sensor	1/4" Color CMOS Sensor			
Pixel Resolution	640(H) x 480(V)			
Minimum Illumination	1.5 Lux @ F2.0			
Electronic Shutter	1/60~1/150,000sec	1/50~1/150,000sec	1/60~1/150,000sec	1/50~1/150,000sec
Auto Gain Control	Automatic			
Auto White Balance	Automatic			
Lens	4.0mm Fixed Focal with Fine Tuning / F2.0			
Pan / Tilt	Motorized Pan 35° / Motorized Tilt 135°			
Image Compression	MPEG4 SP (Simple Profile) / JPEG for Still Images			
Image Frame Rate	Up to 30/25 fps @ 160x120; Up to 30/25 fps @ 320x240; Up to 30/25 fps @ 640x480			
Physical Networking	10 base-T or 100 base-T Fast Ethernet Auto Negotiation			
WLAN Networking	N/A		802.11g Wireless LAN	
Supported Protocol	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, DNS, DHCP and RTSP			
Audio	AAC, GSM-AMR			
Microphone	Omni-directional / Frequency 50~16,000Hz / SN Ratio more than 60dB			
CPU	WTK-1000			
RAM	32MB SDRAM			
ROM	4MB Flash ROM			
Software OS Support	Windows 98SE, ME, 2000, XP			
Supported Browser	Internet Explorer 5.x or above			
Operating Temperature	0°C ~ +50°C / 32°F~122°F			
Operating Humidity	RH95% or less			
Power Supply	Input: 100~240V AC, 50/60Hz, 0.5A / Output: 12V DC, 1.5A			
Power Consumption	7.0W Max.			
Dimension	100(D) x 110(W) x 120(H) mm			
Weight	271g			