

High Resolution Sony CCD IR Camera



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

IR LED: .48PCS ,IR Distance: 100 ft

Water Resistance : IP66

Auto White Balance(AWB)

Lens: Board Lens 6mm/F2.0 or 4mm/F2.0

Dimension : 143(W) x 75(H) x 75(D)mm



Specifications

Model	BIPRO-540L4	BIPRO-540L6	Not Available	Not Available
Image Sensor	1/3"SONY		1/3"SONY	1/4"SHARP
Horizontal Resolution	540 TV Line	540 TV Line	420 TV Line	
Pixels	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:795(H)×596(V) NTSC:811(H)×508(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)	
TV System	PAL/NTSC			
IR LED	48 PCS			
IR Series Distance	100 Feet			
Lens	4mm	6mm		
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
Usable Illumination	0 Lux/F2.0 (LED ON)			
IR Power On	CDS Auto Control			
S/N Ratio	≥48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10°C ~ +50°C RH95% Max			
Storage Temperature	-20°C ~ +60°C RH95% Max			
White Balance	Auto			
Power Source	DC12V 300mA			
Dimension	143(W) x 75(H) x 75(D)mm			
Weight	750g			