

Portable 8" Portable LCD Monitor

Model: MON-8TM



8" Portable LCD Monitor Features:

- 8-inch TFT LCD monitor
- Composite BNC Video Input
- VGA Video Input
- Can be used as a CCTV service monitor to test cameras
- Can be used as a portable or permanent small LCD monitor
- VGA interface makes it compatible to be a small computer monitor or DVR monitor
- VESA 75 Wall Mount Compatible
- Small Desktop Kick Stand included
- LCD screen size: 8 inch, 183 x 141mm
- LCD active area: 162.0 x 121.5mm
- LCD drive system: A-Si TFT active matrix
- LCD screen color: 262K colors by 6 Bit R.G.B.
- LCD dot matrix: horizontal 800 x 3 (RGB) x vertical 600 dots
- LCD dot pitch: 0.2025 x 0.2025mm
- Overall dimension (W x H X D): 200.98 x 199.98 x 51.2mm
- Contract ratio: 500:1
- Luminosity: 25cd/m²
- Sound output: 1W x built-in 2.7cm speaker 2 pieces



- Input terminal: power input, video input, and audio input
 - Consumption power: 12V DC/650mA, 8W maximum
 - Power input: 12V DC $\pm 10\%$
 - Video input: 0.75Vp-p to 1Vp-p, pin3.5 Φ
 - Audio input: 50m V.(minimum), stereo in, pin3.5 Φ
 - Sound output: earphone, pin3.5 Φ
 - Screen display: normal/reverse switchable (N \leftrightarrow R)
 - Operate temperature: 5 to 60 $^{\circ}\text{C}$
 - Storage temperature: -40 to +95 $^{\circ}\text{C}$
 - Maximum working hours of the rechargeable battery pack: 4 hours
 - Battery charging time: 2 hours
 - Safety approved: CE, FCC, and RoHS
-
- Portable monitor test kit includes a rechargeable battery pack (with charger, nylon carrying case with shoulder strap, video cable, audio cable).
 - The carrying case is designed to hold the monitor and all accessories, battery pack and cables ready for field use
 - This CCTV camera test kit also includes a power adapter allowing the unit to be used while the battery is being charged