

GV-BX1500 Series 1.3MP H.264 Super Low Lux WDR D/N Box IP Camera

GV-BX1500-0F / 1F / 2F



GV-BX1500-3V



- 1.3 megapixel progressive scan super low lux CMOS
- Dual streams from H.264 and MJPEG
- Up to 30 fps at 1280 x 1024
- Built-in / external microphone
- 2-way audio
- One sensor input and alarm output
- TV-out support
- Built-in Micro SD (SDHC / SDXC) card slot for local storage
- Mini USB slot for WiFi Adapter or USB hard drive
- Wide Dynamic Range (WDR)
- Defog
- Motion detection
- Tampering alarm
- Privacy mask
- IP address filtering
- DC 12V / PoE
- Removable IR-cut filter for Day/Night function
- Varifocal megapixel lens
- Supports iPhone, iPad, Android & 3GPP
- 31 languages on Web interface
- ONVIF (Profile S) conformant

* No Memory card slot & local storage function for Argentina.

Introduction

The GV-BX1500 is a series of indoor IP cameras containing a varifocal model and several fixed focal models. The camera is equipped with a Super Low Lux CMOS image sensor which allows the live view to be seen at near darkness. The camera features a mini USB port which supports wireless connection through a GV-WiFi Adapter (optional) or external storage using a USB hard drive.

Models

Models	Iris	Focal Length (mm)	Maximum Aperture	Image Format
BX1500-0F	Fixed	4 mm	F/1.5	1/3"
BX1500-1F		8 mm	F/1.6	1/2.5"
BX1500-2F		12 mm		
BX1500-3V	DC drive	2.8 ~ 12 mm	F/1.5	1/3"

Active Tampering Alarm

Tampered



Focus Change



Camera Shift












Antenna Type	External	
Security	WEP, WPA-PSK(TKIP), WPA-PSK(AES), WPA2-PSK(TKIP), WPA2-PSK(AES)	
Mechanical		
Temperature Detector	Yes	
	Power	2-pin terminal block, PoE
	Ethernet	RJ-45
	Audio	1 In (Using the built-in microphone or externally connecting a microphone) 1 Out (Stereo phone jack, 3.5 mm / 0.14")
Connectors	Digital I/O	3-pin terminal block, pitch 2.5 mm (0.1")
	Auto Iris	Yes
	Local Storage	Micro SD memory card slot (SDHC / SDXC for Class 6 card or above)
	TV-Out	BNC connector (640 x 480 resolution)
	Mini USB	GV-WiFi Adapter or USB hard drive
LED Indicator	2 LEDs: Power, Status	
General		
Operating Temperature	0 °C ~ 50 °C (32 °F ~ 122 °F)	
Humidity	10% to 90% (no condensation)	
Power Source	12V DC / PoE	
Max. Power Consumption	9.5W	
Dimensions (without lens)	75.5 x 75 x 54 mm (2.97" x 2.95" x 2.13")	
Weight	300 g (0.66 lb)	
Regulatory	CE, RCM, FCC, RoHS compliant	
Power over Ethernet		
PoE Standard	IEEE 802.3af Class 3 Power over Ethernet / PD	
PoE Power Supply Type	End-Span	
PoE Power Output	Per Port 48V DC, 350mA. Max. 15.4 watts	
Web Interface		
Installation Management	Web-based configuration	
Maintenance	Firmware upgrade through Web Browser or Utility	
Access from Web Browser	Camera Live View, Video Recording, Change Video Quality, Bandwidth Control, Image Snapshot, Digital I/O control, Audio, Picture in Picture, Picture and Picture, Privacy Mask, Visual Automation, Tampering Alarm, Text Overlay, Digital PTZ	
Language	Arabic / Bulgarian / Czech / Danish / Dutch / English / Finnish / French / German / Greek / Hebrew / Hungarian / Indonesian / Italian / Japanese / Lithuanian / Norwegian / Persian / Polish / Portuguese / Romanian / Russian / Serbian / Simplified Chinese / Slovakian / Slovenian / Spanish / Swedish / Thai / Traditional Chinese / Turkish	
Applications		
Network Storage	GV-NVR, GV-System, GV-Backup Center, GV-Recording Server	
Smart Device Access	GV-Eye for Android smartphone, tablet, iPhone, and iPod Touch GV-Eye HD for iPad	
Live Viewing	IE, mobile phone	
CMS Server support	GV-Control Center, GV-Center V2, GV-VSM	

Note:

- The signal range and data throughput may vary depending on the network conditions and environmental factors.
- Mind the following limitations and requirements for the mini USB port:
 - The USB hard drive must be of 2.5" or 3.5", version 2.0 or above
 - The USB hard drive's storage capacity must not exceed 2TB
 - USB flash drives and USB hubs are not supported
 - External power supply is required for the USB hard drive
 - To connect a GV-WiFi Adapter, make sure it is connected before the camera is powered on.
- Specifications are subject to change without notice.

Accessories

Name		Details																				
GV-IR LED T2		Weight: 140 g / 0.31 lbs Dimensions (H x W x D): 49 x 47 x 67 mm / 1.93 x 1.85 x 2.64 in																				
GV-PA191 PoE Adapter		Weight: 130 g / 0.29 lb Dimensions (H x W x D): 43 x 69 x 40 mm / 1.69 x 2.72 x 1.57 in																				
GV-Relay V2		The GV-Relay V2 is designed to expand the voltage load of GV IP devices. It provides 4 relay outputs, and each can be set as normally open (NO) or normally closed (NC) independently as per your requirement.																				
Power Adapter		Power adapters are available in 4 regions: U.S.A., Australia, U.K and Europe.																				
GV-WiFi Adaptor		Weight: 20 g / 0.04 lb Dimensions: 15 x 15 x 155 mm / 0.59" x 0.59" x 6.10" Supplied with mini USB to standard USB adapter.																				
Fixed Lens : 4 mm		<table border="1"> <tbody> <tr> <td data-bbox="915 1247 1024 1272">Description</td> <td data-bbox="1084 1247 1325 1272">Megapixel day/ night lens</td> </tr> <tr> <td data-bbox="915 1297 1036 1323">Focal Length</td> <td data-bbox="1084 1297 1143 1323">4 mm</td> </tr> <tr> <td data-bbox="915 1348 1013 1373">Maximum Aperture</td> <td data-bbox="1084 1373 1143 1398">F/1.5</td> </tr> <tr> <td data-bbox="915 1444 980 1470">Mount</td> <td data-bbox="1084 1444 1179 1470">CS Mount</td> </tr> <tr> <td data-bbox="915 1495 1049 1520">Image Format</td> <td data-bbox="1084 1495 1127 1520">1/3"</td> </tr> <tr> <td data-bbox="915 1600 1013 1625">Operation</td> <td data-bbox="1084 1549 1224 1575">Focus: Manual</td> </tr> <tr> <td></td> <td data-bbox="1084 1600 1201 1625">Zoom: Fixed</td> </tr> <tr> <td></td> <td data-bbox="1084 1650 1179 1675">Iris: Fixed</td> </tr> <tr> <td data-bbox="915 1701 1019 1726">Dimension</td> <td data-bbox="1084 1701 1360 1726">ø30 x 27 mm / ø1.18 x 1.06 in</td> </tr> <tr> <td data-bbox="915 1751 987 1776">Weight</td> <td data-bbox="1084 1751 1208 1776">30 g / 0.07 lb</td> </tr> </tbody> </table>	Description	Megapixel day/ night lens	Focal Length	4 mm	Maximum Aperture	F/1.5	Mount	CS Mount	Image Format	1/3"	Operation	Focus: Manual		Zoom: Fixed		Iris: Fixed	Dimension	ø30 x 27 mm / ø1.18 x 1.06 in	Weight	30 g / 0.07 lb
Description	Megapixel day/ night lens																					
Focal Length	4 mm																					
Maximum Aperture	F/1.5																					
Mount	CS Mount																					
Image Format	1/3"																					
Operation	Focus: Manual																					
	Zoom: Fixed																					
	Iris: Fixed																					
Dimension	ø30 x 27 mm / ø1.18 x 1.06 in																					
Weight	30 g / 0.07 lb																					

Name		Details																
Fixed Lens : 8 mm		<table border="1"> <tr><td>Description</td><td>Megapixel day/ night lens</td></tr> <tr><td>Focal Length</td><td>8 mm</td></tr> <tr><td>Maximum Aperture</td><td>F/1.6</td></tr> <tr><td>Mount</td><td>CS Mount</td></tr> <tr><td>Image Format</td><td>1/2.5"</td></tr> <tr><td>Operation</td><td>Focus: Manual Zoom: Fixed Iris: Fixed</td></tr> <tr><td>Dimension</td><td>ø 30 x 19.6 mm / ø 1.18 x 0.77 in</td></tr> <tr><td>Weight</td><td>27.7 g / 0.06 lb</td></tr> </table>	Description	Megapixel day/ night lens	Focal Length	8 mm	Maximum Aperture	F/1.6	Mount	CS Mount	Image Format	1/2.5"	Operation	Focus: Manual Zoom: Fixed Iris: Fixed	Dimension	ø 30 x 19.6 mm / ø 1.18 x 0.77 in	Weight	27.7 g / 0.06 lb
Description	Megapixel day/ night lens																	
Focal Length	8 mm																	
Maximum Aperture	F/1.6																	
Mount	CS Mount																	
Image Format	1/2.5"																	
Operation	Focus: Manual Zoom: Fixed Iris: Fixed																	
Dimension	ø 30 x 19.6 mm / ø 1.18 x 0.77 in																	
Weight	27.7 g / 0.06 lb																	
Fixed Lens : 12 mm		<table border="1"> <tr><td>Description</td><td>Megapixel day/ night lens</td></tr> <tr><td>Focal Length</td><td>12 mm</td></tr> <tr><td>Maximum Aperture</td><td>F/1.6</td></tr> <tr><td>Mount</td><td>CS Mount</td></tr> <tr><td>Image Format</td><td>1/2.5"</td></tr> <tr><td>Operation</td><td>Focus: Manual Zoom: Fixed Iris: Fixed</td></tr> <tr><td>Dimension</td><td>ø 30 x 20.6 mm / ø 1.18 x 0.81 in</td></tr> <tr><td>Weight</td><td>28.6 g / 0.06 lb</td></tr> </table>	Description	Megapixel day/ night lens	Focal Length	12 mm	Maximum Aperture	F/1.6	Mount	CS Mount	Image Format	1/2.5"	Operation	Focus: Manual Zoom: Fixed Iris: Fixed	Dimension	ø 30 x 20.6 mm / ø 1.18 x 0.81 in	Weight	28.6 g / 0.06 lb
Description	Megapixel day/ night lens																	
Focal Length	12 mm																	
Maximum Aperture	F/1.6																	
Mount	CS Mount																	
Image Format	1/2.5"																	
Operation	Focus: Manual Zoom: Fixed Iris: Fixed																	
Dimension	ø 30 x 20.6 mm / ø 1.18 x 0.81 in																	
Weight	28.6 g / 0.06 lb																	
Varifocal Lens : 2.8 ~ 12 mm		<table border="1"> <tr><td>Description</td><td>Megapixel day/ night lens</td></tr> <tr><td>Focal Length</td><td>2.8 ~ 12 mm</td></tr> <tr><td>Maximum Aperture</td><td>F/1.4</td></tr> <tr><td>Mount</td><td>CS Mount</td></tr> <tr><td>Image Format</td><td>1/3"</td></tr> <tr><td>Operation</td><td>Focus: Manual (w/lock) Zoom: Manual (w/lock) Iris: DC Drive</td></tr> <tr><td>Dimension</td><td>ø 43 x 44 mm / ø 1.69 x 1.73 in</td></tr> <tr><td>Weight</td><td>72 g / 0.16 lb</td></tr> </table>	Description	Megapixel day/ night lens	Focal Length	2.8 ~ 12 mm	Maximum Aperture	F/1.4	Mount	CS Mount	Image Format	1/3"	Operation	Focus: Manual (w/lock) Zoom: Manual (w/lock) Iris: DC Drive	Dimension	ø 43 x 44 mm / ø 1.69 x 1.73 in	Weight	72 g / 0.16 lb
Description	Megapixel day/ night lens																	
Focal Length	2.8 ~ 12 mm																	
Maximum Aperture	F/1.4																	
Mount	CS Mount																	
Image Format	1/3"																	
Operation	Focus: Manual (w/lock) Zoom: Manual (w/lock) Iris: DC Drive																	
Dimension	ø 43 x 44 mm / ø 1.69 x 1.73 in																	
Weight	72 g / 0.16 lb																	