



# Mini-Box Network Camera IP8152/52-F4





1.3MP • Compact Size • Supreme  
Night Visibility

VIVOTEK IP8152/52-F4 features a brand new box camera design concept from VIVOTEK, with a compact size and a multitude of features. The small size makes it an easy to fit into different types of enclosures with different lens options, with the ability to fit a CS-mount lens making it a flexible solution for all types of surveillance. The Supreme Night Visibility features results in excellent video quality in low light environments; pairing with the built-in IR-cut filter further increase the range of visibility at night by allowing the use of IR illuminators. With all of these features and more, the camera is especially suitable for city surveillance, retail stores, government, industrial applications or hotel security.

The IP8152/52-F4 supports the industry-standard H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. Together with the ST7501 multi-lingual 32-channel recording software, users can set up an easy-to-use IP surveillance system with ease.

## Features

- 1.3-Megapixel CMOS Sensor
- Compact Design
- Real-time H.264 and MJPEG Compression (Dual Codec)
- 30fps @ 1280x1024
- Supreme Night Visibility
- Two-way Audio
- Removable IR-cut Filter for Day and Night Function
- Built-in IEEE 802.3af Compliant PoE
- Built-in MicroSD/SDHC Card Slot for On-board Storage



## Technical Specifications

<b>Models</b>	IP8152 (Vari-focal) IP8152-F4 (Fixed-focal)	<b>Intelligent Video</b>	Video Motion Detection Triple-window video motion detection
<b>System Information</b>		<b>Alarm and Event</b>	
CPU	Multimedia SoC (System-on-Chip)	<b>Alarm Triggers</b>	Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection
Flash	16 MB	<b>Alarm Events</b>	Event notification using HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server
RAM	256 MB	<b>General</b>	
<b>Camera Features</b>		<b>Connectors</b>	RJ-45 for Network/PoE connection Audio input Audio output RS485*1 Digital input*1
Image Sensor	1/3" Progressive CMOS	<b>LED Indicator</b>	System power and status indicator
Maximum Resolution	1280x1024	<b>Power Input</b>	IEEE 802.3af PoE Class 2
Lens Type	Vari-focal (IP8152) Fixed-focal (IP8152-F4)	<b>Power Consumption</b>	Max. 3.4W
Focal Length	f = 3.3 ~ 12 mm (IP8152) f = 4 mm (IP8152-F4)	<b>Dimensions</b>	39mm (D) x 80mm (W) x 70mm (H) (Body only) 88mm (D) x 80mm (W) x 70mm (H) (IP8152) 52mm (D) x 80mm (W) x 70mm (H) (IP8152-F4)
Aperture	F1.4 (wide), F2.4 (tele) (IP8152) F1.6 (IP8152-F4)	<b>Weight</b>	176 g (Body only) 233 g (IP8152 with lens) 202 g (IP8152-F4 with lens)
Auto-iris	DC-iris (IP8152) Fixed-iris (IP8152-F4)	<b>Safety Certifications</b>	CE, LVD, FCC Class B, VCCI, C-Tick
Field of View	IP8152: 34° ~ 74° (horizontal) 25° ~ 60° (vertical) 40° ~ 95° (diagonal) IP8152-F4: 76° (horizontal) 60° (vertical) 99° (diagonal)	<b>Operating Temperature</b>	0°C ~ 50°C
Shutter Time	1/15 sec. to 1/25,000 sec.	<b>Warranty</b>	24 months
Day/Night	Removable IR-cut filter for day & night function	<b>System Requirements</b>	
Minimum Illumination	IP8152: 0.11 Lux @ F1.4 (Color) 0.001 Lux @ F1.4 (B/W) IP8152-F4: 0.12 Lux @ F1.6 (Color) 0.001 Lux @ F1.6 (B/W)	<b>Operating System</b>	Microsoft Windows 7/Vista/XP/2000
Pan/tilt/zoom	ePTZ:	<b>Web Browser</b>	Mozilla Firefox 7~10 (streaming only) Internet Explorer 7.x or 8.x
Functionalities	48x digital zoom (4x on IE plug-in, 12x built-in)	<b>Other Players</b>	VLC: 1.1.11 or above QuickTime: 7 or above
On-board Storage	Micro SD/SDHC/SDXC card slot	<b>Included Accessories</b>	
<b>Video</b>		<b>CD</b>	User's manual, quick installation guide, Installation Wizard 2, ST7501 32-channel recording software
Compression	H.264 & MJPEG	<b>Others</b>	Quick installation guide, warranty card, lens, camera stand, screw pack
Maximum Frame Rate	H.264: 30 fps at 1280x1024 MJPEG: 30 fps at 1280x1024	<b>Dimensions</b>	
Maximum Streams	2 simultaneous streams	• IP8152	
S/N Ratio	Above 58 dB	• IP8152-F4	
Dynamic Range	67 dB	Image Settings Adjustable resolution, quality and bitrate Configurable video cropping for bandwidth saving Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings	
Video Streaming	Adjustable resolution, quality and bitrate Configurable video cropping for bandwidth saving	<b>Audio</b>	
Image Settings	Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings	Audio Capability Audio input/output (full duplex)	
<b>Audio</b>		Compression G.711	
Audio Capability Audio input/output (full duplex)		Interface External microphone input External line output	
<b>Network</b>		Users Live viewing for up to 10 clients	
Users Live viewing for up to 10 clients		Protocols IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X	
Interface 10Base-T/100 BaseTX Ethernet (RJ-45)		ONVIF Supported, specification available at www.onvif.org	

## Compatible Accessories

### Mounting Kits



**AE-211**  
Camera enclosure with blower

**AE-232**  
Camera enclosure with heater and blower

**AE-233**  
Camera enclosure with heater and blower (input AC 24V)

**AE2000**  
Infrared illuminator enclosure

### PoE Kits



**AE-151**  
Outdoor dome housing



**MS-POE-IJAF**  
PoE injector, 802.3af compliant



**AE-101**  
Indoor camera enclosure with transparent cover

**AE-102**  
Indoor camera enclosure with smoke cover



**AE-131**  
Outdoor dome housing with transparent cover

**AE-132**  
Outdoor dome housing with smoke cover

### Lens



**AL-231**  
2.8 ~ 12mm, F1.2, DC-iris



**AL-234**  
5mm~50mm, F1.6, DC-iris

All specifications are subject to change without notice. Copyright © 2012 VIVOTEK INC. All rights reserved.

Distributed by:



VIVOTEK INC.

6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C.  
| T: +886-2-82455282 | F: +886-2-82455532 | E: sales@vivotek.com

VIVOTEK USA, INC.

2050 Ringwood Avenue, San Jose, CA 95131  
| T: 408-773-8888 | F: 408-773-8298 | E: salesusa@vivotek.com

Ver 1.0