

B5210 HD 1080p Megapixel Day/Night Bullet IP Camera



- Megapixel 1080P HD resolution
- Multiple H.264, Motion JPEG and MPEG-4
 video streams
- True day/night with automatic removable
 IR-cut filter
- MicroSD card slot
- O Power over Ethernet
- Easy install with a variety function of three-axis bracket
- 2 Megapixel CMOS image sensor
- Multiple H.264, Motion JPEG, MPEG-4 and 3GPP video streams
- 4.0mm, F1.8 megapixel fixed lens
- 30 fps in 1920 x 1080
- True day/night capabilities with automatic removable IR-cut filter
- Build-in IR LED illuminators with adjustable brightness and 15m working distance
- Enhanced high contrast bright & dark with WDR
- Analog video output through BNC connector
- MicroSD card local storage
- Power over Ethernet (IEEE 802.3af)
- IP67 rated weatherproof housing
- SSL v3 advanced HTTPS encryption
- Full support for Firefox, Safari and Mac OS
- 32 channel ZAVIO CamGraba NVR software
- Multi-lingual user interface
- ONVIF compatible

Technical Specifications

Camera	
Models	B5210 1080p 2 megapixel day/night bullet IP camera
Image sensor	1/2.7" progressive scan CMOS 2 megapixel sensor
Lens	F1.8, 4.0 mm, fixed lens
Angle of view	77° horizontal
Digital zoom	10x digital
Min illumination	0.2 Lux at F1.8
IR working distance	15m effective range
IR LEDs	High performance IR LED x 3 (850nm)
Day/Night function	Mechanical IR cut filter
Shutter time	1/2 ~ 1/10,000 sec.
S/N ratio	39dB
Video	
Video compression	Motion JPEG MPEG-4 part 2 (ISO/IEC 14496-2) simple profile H.264 baseline profile
Resolutions	Motion JPEG: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page MPEG-4: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page H.264: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page
Frame rate	Motion JPEG: up to 30 fps at 1920 x 1080 MPEG-4: up to 30 fps at 1920 x 1080 H.264: up to 30 fps at 1920 x 1080
Video streaming	Simultaneous Motion JPEG, MPEG-4, H.264 and 3GPF (multiple streaming) Controllable frame rate and bandwidth Support unicast and multicast Support 3GPP/ ISMA RTSP (Real Time Streaming Protocol)
Image settings	Brightness, contrast, saturation WDR enhanced Rotation: mirror, flip, mirror flip Overlay capabilities: time, date, text and privacy Image
Network	
Security	Multiple user access levels with password protection, HTTPS encryption
Supported protocols	Bonjour, TCP/ IP, DHCP, DNS, DynDNS, PPPOE, ARP, ICMP, FTP, SMTP, NTP, UPnP, RTSP, RTP, RTCP, HTTP, HTTPS, SSL, TCP, UDP, 3GPP/ ISMA
Users	10 simultaneous users Unlimited number of users using multicast
Alarm and Event	Support
Alarm and event management	Input: motion detection Output: network storage, FTP, SMTP, pre-and post alarm buffer
System	
Connectors	RJ-45 Ethernet 10/ 100 Base-T (PoE) DC power Jack Analog video output
Local storage	MicroSD Card slot
LED Indicator	Power status indicator Network link indicator MicroSD card status indicator
General	
Casina	Aluminum casing

Housing	Weatherproof IP67-rated
Power	12V DC, 1A, Max 12W
Operating conditions	-10 ~ 50°C (14 ~ 122°F)
Installation, management, and maintenance	ZAVIO camera management tool on CD and web-based configuration. Configuration of backup and restore firmware upgrades over HTTP, firmware available at www.zavio.com
Minimum web browsing requirement	Pentium 4 2.8GHz (or equivalent AMD) 256MB RAM graphic cards (or equivalent on-board graphic cards) 1G RAM Window 2000, 2003, XP, Vista or Windows 7 Mac OS Leopard 10.5 or later
Dimensions (HxWxD)	270x 69(φ) mm (10.6" x 2.7")
Weight	900g (1.98lb) excl. power supply
Included accessories	Quick installation guide, CD (IP surveillance software, intelligent IP installer, user manuals, and language packs), mounting and connector kits, power supply 12V DC
Certification	CE, FCC, RoHS
Integration	
Video management software	ZAVIO CamGraba IP System software, for viewing, recording and archiving up to 32 cameras See http://www.zavio.com/suport_softwares.php For more software application





Aluminum casing

Casing