

## **B7210 2 Megapixel Bullet IP Camera**



- 2 Megapixel CMOS Sensor
- 4 High Performance IR LEDs and35m Working Distance
- Built-in MicroSD/ SDHC Card Slot for Local Storage
- Built-in Heater and Fan
- Enhances High Contrast Bright & Dark with
   WDR
- Supports True Plug and Play Cloud Solution
- 2 megapixel progressive scan CMOS sensor
- H.264, Motion JPEG, MPEG-4 and 3GPP video streams
- 30 fps in 1920 x 1080
- Day/night functionality with automatic removable IR-cut filter
- 4 high performance IR LEDs and 35m distance
- 3 9mm, F1.2 varifocal, auto-iris lens
- Enhances high contrast bright & dark with WDR
- Analog video output through RCA connector
- MicroSD/ SDHC card local storage
- Built-in heater and fan, enabling camera in severe environment (-40 ~ 60°C)
- Power over Ethernet (IEEE 802.3af)
- 2 x alarm input, 2 x alarm output
- IP66 rated weatherproof housing
- SSL v3 advanced HTTPS encryption
- Camera tampering detection support
- Supports Samba network storage
- 3GPP mobile surveillance
- 64 channel ZAVIO CamGraba 2.0 NVR software
- Multi-lingual user interface
- ONVIF compatible

## Datasheet 2 Bullet IP Camera

## **Technical Specifications**

Camera	
Models	B7210 2 Megapixel Bullet IP Camera
Image sensor	1/2.7" progressive scan CMOS 2 megapixel sensor
Lens	F1.2, 3 ~ 9mm, vari-focal, auto-iris
Angle of view	38° ~ 121° horizontal
Aligie of view	21° ~ 62° vertical
Digital zoom	10x digital
Min illumination	0 lux at F1.2 (IR LED on)
IR working distance	35m effective range
IR LEDs	High performance IR LED x 4 (850nm)
Day/Night function	Mechanical IR cut filter
Shutter time	1/2 ~ 1/10000sec.
S/N ratio	39dB
Video	
Video compression	Motion JPEG, MPEG-4, H.264
Resolutions	Motion JPEG: 8 resolutions from 1920 x 1080 to 160 x 120 via API, 8 selections via configuration web page MPEG-4: 8 resolutions from 1920 x 1080 to 160 x 120 via API, 8 selections via configuration web page H.264: 8 resolutions from 1920 x 1080 to 160 x 120 via API, 8 selections via configuration web page
Frame rate	Motion JPEG: up to 30 fps at 1920 x 1080 MPEG-4: up to 30 fps at 1920 x 1080 H.264: up to 30 fps at 1920 x 1080
Video streaming	Simultaneous Motion JPEG, MPEG-4, H.264 and 3GPP (multiple streaming) Controllable frame rate and bandwidth Support unicast and multicast Support 3GPP/ ISMA RTSP (Real time streaming protocol)
Image settings	Brightness, contrast, saturation WDR enhanced Rotation: mirror, flip, mirror flip Overlay capabilities: time, date, text and privacy image
Audio	
Audio streaming	Two-way (full duplex) Line in & out
Audio compression	G.711 μ law, a law, AMR
Network	
Security	Multiple user access levels with password protection HTTPS encryption
Supported protocols	Bonjour, TCP/IP, DHCP, PPPOE, ARP, ICMP, FTP, SMT DNS, NTP, UPnP, RTSP, RTP, RTCP, HTTP, HTTPS, SSL TCP/IP, UDP, 3GPP/ISMA RTSP, IGMP, DynDns
Users	10 simultaneous users Unlimited number of users using multicast
Alarm and Event	
Alarm and event management	Input: alarm buffer, motion detection, audio detection, tampering detection Output: network storage, FTP, SMTP, pre-and post alarm buffer
System	
Connectors	RJ-45 for Ethernet 10/100 Base-T (with PoE) 2 pin terminal blocks for DC power Terminal blocks for 2 alarm input, 2 alarm output, Audio line input, Audio line output Reset push switch

RCA connector for analog video output

LED Indicator	System power status indicator Network link indicator MicroSD/ SDHC card status indicator
General	
Casing	Aluminum casing
Housing	Weatherproof IP66-rated
AC power requirement & consumption	Power requirement: 12V DC, 1.5A, Max. 12W Note: while IR on, heater or fan would be activated automatically
PoE power requirement & consumption	Power requirement: Power over Ethernet IEEE 802.3af Note: while IR on, heater and fan will be disabled
Heater & fan	Built-in and auto activation Note: Heater will be activated while the B7210 inner temperature drops under $5^\circ\!\!C$ and fan over $50^\circ\!\!C$
Operating conditions	-40 ~ 60°C (-40 ~ 140°F)
Installation, management, and maintenance	ZAVIO camera management tool on CD and web-based configuration. Configuration of backup and restore firmware upgrades over HTTP, firmware available at www.zavio.com
Minimum web browsing requirement	Pentium 4 2.8GHz (or equivalent AMD) 256 MB RAM graphic cards (or equivalent on-board graphic cards) 1G RAM Window 2000, 2003, XP, Vista or Windows 7 Mac OS Leopard 10.5
Dimensions (HxWxD)	360 x 125 x 250mm (14.2" x 4.9" x 9.8")
Weight	1830.8g (4.05lb) excl. power supply
Included accessories	Quick installation guide, CD (IP Surveillance Software, Intelligent IP Installer, user manuals, and language pack), mounting and connector kits Note: AC power supply not included
Certification	CE, FCC, RoHS
Integration	
Video management software	ZAVIO CamGraba IP System software, for viewing, recording and archiving up to 64 cameras See http://www.zavio.com/product.php?id=50

## for more software application Physical Description PIN1~8: Ground Digital Output:

PIN1~8: Ground, +12VDC, DI, DO Digital Output 1, Digital Output 2, Alarm Input 1, Alarm Input 2

