

# D6210 | Eyeball Dome 2MP Outdoor IR Eyeball Camera

www.zavio.com

**ZAVIO**  
Innovating IP since 2006



- 1/2.8" 2MP CMOS sensor
- Fixed lens 2.8mm, F2.0
- 1080p @ 30fps
- 3D DNR
- 30m IR range
- ROI (Region Of Interest)
- Corridor mode
- Operating conditions -30~ 60°C
- 12V DC & PoE (802.3af)
- IP66
- ONVIF 2.4 & Profile S

ZAVIO D6210 is an outdoor ready IR eyeball dome, with 2MP resolution and frame rate of up to 30fps @ 1080p. Featuring ROI (Region of Interest) and Corridor mode, allowing you to spend your precious bandwidth and storage on the areas that really matter and helping you to make the most of your field of view by changing the standard landscape mode into corridor mode for staircases, aisles, tunnels and many more.

Compatible with ZAVIO CamGraba 2.0, the most professional free NVR software that can support up to 64 IP cameras.

## Optional accessories

**Accessory:** Junction box  
**Item number:** AZ-M01  
**Dimensions:** 119 x 39mm  
**Compatible with:** D6210, D6320, D6520, B6210, B6320, B6520, B6220, B6330, B6530,

Junction box



D6210 with junction box



## Features

### ROI (Region Of Interest)

Defining a Region Of Interest will allow you to spend less bandwidth in areas that are less important while relocating resolution on the most relevant areas.



**Landscape mode**

**Corridor mode**

### Corridor mode

Corridor Mode allows you to get a vertically oriented video stream from the camera, maximizing image quality while eliminating bandwidth and storage waste.

## Technical Specifications

### Camera

Camera Type	2MP Outdoor IR Eyeball Dome
Image sensor	1/2.8" CMOS sensor
Lens	Fixed lens 2.8mm, F2.0
Horizontal view angle	96°
IR working distance	30m effective range
Min illumination	0.05 lux @ F2.0 (color) 0.005 lux @ F2.0 (B/W)
WDR	D-WDR
Day/Night function	Mechanical IR cut filter, Light sensor

### Video & Audio

Resolutions	Motion JPEG/H.264: 2 Profile from 1920 x 1080 to 320 x 240 (total 5 resolutions) 2 Profile from 640 x 480 to 320 x 240 (total 3 resolutions)
Video compression	Motion JPEG H.264 baseline/ main profile/high profile -
Frame rate	H.264: up to 30 fps at 1920 x 1080 Motion JPEG : up to 30 fps at 1920 x 1080
Video streaming	Simultaneous Motion JPEG, H.264 Controllable frame rate and bandwidth Support unicast (Real Time Streaming Protocol)
Image settings	Rotation: mirror, flip, mirror flip, corridor mode Brightness, contrast, saturation, sharpness Overlay capabilities: time, date, text and privacy Image ROI 3D DNR -
Audio support	-
Audio compression	-

### I/O & Connector

Ethernet	RJ-45 Ethernet 10/100 Base -T
Power Supply	DC Jack, 12V DC, 1A Power consumption: Max 6.6W PoE(Power over Ethernet) built-in IEEE 802.3af
Alarm I/O	-
Audio connector	-
Analog video output	-
RS-485	-
Edge storage	-
Buttons	Reset push button
Other(s)	-

### Alarm & Event

Input	Alarm buffer, alarm input, motion detection, periodical, network link down.
Output	Network storage, FTP, SMTP, HTTP event, HTTPS, alarm out pre and post event image.

### Network

Users	5 simultaneous users
Security	Multiple user access levels with password protection, HTTPS encryption
Supported protocols	IPv4, IPv6, Bonjour, TCP/IP, DHCP, DNS, DynDNS, PPPoE, ARP, ICMP, FTP, SMTP, NTP, UPnP, RTSP, RTP, RTCP, HTTP, HTTPS, SSL, TCP, UDP
ONVIF	2.4 & Profile S

### General

Housing	Aluminum Alloy
Ingress Protection	IP66 rated weatherproof housing
Impact Protection	-
Other(s)	-
Operating conditions	Starting temperature: -10 ~ 60°C Humidity 10-100% RH Working temperature: -30~ 60°C Humidity 10-100% RH
Dimensions(HxWxD)	56.8 x 119.24 x 82.79mm
Weight	710g excl. power supply
Included accessories	Quick installation guide, mounting and connector kit.
Optional accessories	Junction box
Certification	CE, FCC, RoHS
Language	Chinese, Croatian, Czech, Danish, Dutch, English, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Slovak, Spanish, Swedish, Turkish

### System Requirements

Operating system	Windows XP / 7 / 8 / 8.1, MAC OS, Linux
Browser	Internet Explorer 9 / 10 / 11, Chrome, Firefox, Safari

### Software

Video management software	ZAVIO CamGraba 2.0 IP System software, for viewing, recording and archiving up to 64 cameras.
Installation, management and maintenance	ZAVIO Installation Tool makes camera management easier with camera image preview, firmware upgrade of multiple cameras, reset cameras to default while keeping network settings, etc.

