

PTZ-HD-10

10x HD-TVI, HDCVI, AHD, Analog CCTV IR PTZ



Camera Major Features

- 4in1 Selectable IR PTZ Camera
- 1080p Modes: HD-TVI, AHD, HDCVI
- 960H Analog CCTV Mode (CVBS)
- 10x Optical Zoom
- 150ft Infrared Rating
- IP66 Weatherproof Housing
- PTZ Speed Dome with full function
- 360° endless rotation
- Preset / Scan / Tour / Park
- True Day & Night
- Dual Voltage DC12V / AC24V

Model	PTZ-HD-10
Camera	
Image Sensor	1/3" progressive scan, Sony CMOS
Effective Pixels	1080P (1920x 1080)
Resolution	1920x1080 @ 30fps
S/N Ratio	>50dB
Zoom Ratio	10x Optical zoom
Focal Length	f=5.1(Wide) ~51(Tele)mm
Field of view	H : 51.8°(W)~5.86°(T) V : 39.1°(W)~4.4°(T)
Mini Illumination	0.01Lux/F1.8 (0Lux with IR on)
Day/Night	ICR, Auto
IRs	6 Array IRs(1.7inch), 150ft
IR control	15 grade selectable
Focus	Auto
AGC	On
White Balance	Auto
WDR	DWDR
Video Output	TVI/CVI/AHD/CVBS selectable
PTZ	
Pan/Tilt Range	Pan 360°Endless, Tilt: 0~93°
Manual Speed	Pan: 0.02°/Sec~200°/Sec Tilt: 0.02°/Sec~120°/Sec
Preset Speed	Max 220°/Sec
Preset	220
Auto Scan	AB Scan, 360 Scan
Park Action, Power on Action	Memory/Home/Tour 1-3/360 scan/ AB scan//None
Tour	3 Group (Max16 Preset)
Auto Flip	Yes
Communication	UTC(coax), RS-485
Protocol	Coaxtron, Pelco-D、Pelco-P
General	
Input Voltage	DC12V/AC24V
Max. Power Consumption	9W(IR off) / 25W(IR on)
Dimension	Φ6" dome x8.5" height
Weight	7.4 lbs
Operating Temp.	-40°F~ 140°F(-40℃~ 60℃)
Work. Humidity	0%~95% (Non-condensation)
Waterproof	IP66
Fan and Heater	Auto temperature control
Lightning Protection	Transient voltage 6000V