


# ZAVIO P6210 2MP Pan/ Tilt IR Mini Dome

**ZAVIO**  
Innovating IP since 2006



- Full HD 1080p
- Sony Exmor sensor
- Motorized pan/ tilt
- True day & night with automatic removable IR-cut filter
- Power over Ethernet
- IK08 vandal-proof



The ZAVIO P6210 is a full HD 1080p Mini Dome camera, can provide 360° x 24 hours full coverage with pan/ tilt and adjustable IR. This 2 megapixel camera has a 1/2.8" SONY CMOS sensor, can be expected to deliver higher video performance.

ZAVIO P6210 has 12 IR illuminator LEDs that enable the camera to see up 10m in zero light when IR LED on. Besides, this camera has a vandal-resistant casing can provide effective protection against tampering. Coupled with its small size (φ115 x 70mm) , motorized pan/ tilt and IK08 vandal-proof, P6210 is designed to allow the camera to be mounted on virtually any flat surface, like walls or ceilings.

Compatible with ZAVIO's free 64 channels NVR software, free mobile video management APP and Plug-and-Play cloud Solution, users can easily setup a surveillance system and 24-7 monitor from mobile devices, PC or laptop without any extra cost.

## Related models

Model Name	P6210	D4210	D3200
Feature	Pan/ tilt IR mini dome	IR mini dome	Mini dome
	Full HD 1080p	Full HD 1080p	Full HD 1080p
	Sony Exmor sensor	Sony Exmor sensor	1/2.7" CMOS
	ICR + IR 10m	ICR + IR 10m	-
	PoE	PoE	PoE
	Motorized pan/ tilt	3-axis	3-axis
	IK08 vandal-proof	IK08 vandal-proof	-

## Features

- Full HD 1080p
- 1/2.8" Sony Exmor CMOS sensor
- H.264 and Motion JPEG compression
- 30 fps in 1920 x 1080
- 3.6mm, F1.8 megapixel fixed lens
- True day & night with automatic removable IR-cut filter and IR LEDs
- Two-way audio and built-in microphone
- Tampering detection
- 1 x alarm input, 1 x alarm output
- RTC with built-in battery
- Excellent PT reliability
- SSL v3 advanced HTTPS encryption
- Supports Firefox, Safari and Mac OS
- Supports Samba network storage
- Multi-lingual user interface
- ONVIF 2.2 and Profile S compliant
- Free 64-channel ZAVIO CamGraba 2.0 NVR software
- Supports True Plug and Play Cloud Solution

## ZAVIO IP Surveillance Solutions

### • Free Plug & Play Cloud Solution

You can watch Live Video on your computer or the mobile app on your iOS/ Android device. Setup is as easy as 1-2-3, and it's completely free!

Step 1. Now, go to [sat.qlync.com](http://sat.qlync.com)

Step 2. Create your account

Step 3. Add cameras to your account

Please go to [zavio.com](http://zavio.com) for a list of Cloud Solution support camera models



### • Free 64ch NVR Software

The most professional NVR software you can get for free!



### • 4ch/ 8ch Standalone NVR

The easiest way to view, record and playback up to 8 Full HD cameras all in real-time.



### • NVR Partners

ZAVIO IP Cameras are supported by a wide range of 3rd party NVR software and devices.



Please go to [zavio.com](http://zavio.com) for a list of our partners.

### • ONVIF

ONVIF 2.2 & Profile S compliant



## Application



1. Retail
2. Home
3. Office

# Technical Specifications

Camera	
<b>Models</b>	P6210 2MP pan/ tilt IR mini dome
<b>Image sensor</b>	1/2.8" megapixel CMOS sensor
<b>Lens</b>	F1.8, 3.6mm
<b>Angle of view</b>	81° horizontal
<b>Digital zoom</b>	10x digital
<b>Min illumination</b>	0.05 lux @ F1.8(color) 0.001 lux (b/w) 0 lux (IR LED on)
<b>IR working distance</b>	10m effective range Adjustable brightness via FW
<b>IR LEDs</b>	5φ x 12 pcs (850nm)
<b>Day/Night function</b>	Mechanical IR cut filter
<b>Pan</b>	330°; speed: 70°/sec. max.
<b>Tilt</b>	67°; speed: 70°/sec. max.

Video	
<b>Video compression</b>	Motion JPEG H.264 baseline profile
<b>Resolutions</b>	Motion JPEG: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page H.264: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page
<b>Frame rate</b>	Motion JPEG: up to 30 fps at 1920 x 1080 H.264: up to 30 fps at 1920 x 1080
<b>Video streaming</b>	Simultaneous Motion JPEG and H.264 (5 streams) Controllable frame rate and bandwidth Support unicast and multicast Support 3GPP/ ISMA RTSP (Real Time Streaming Protocol)
<b>Image settings</b>	Brightness, contrast, saturationcontrast, saturation WDR enhanced Rotation: mirror, flip, mirror flip Overlay capabilities: time, date, text and privacy image

Audio	
<b>Audio streaming</b>	Two-way (full duplex)
<b>Audio compression</b>	G.711 μ law, a law, AMR
<b>Audio input/output</b>	Built-in microphone, line input and line output


Network	
<b>Security</b>	Multiple user access levels with password protection, HTTPS encryption
<b>Supported protocols</b>	Bonjour, TCP/ IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, NTP, UPnP, RTSP, RTP, HTTP, TCP,UDP, 3GPP/ ISMA RTSP
<b>Users</b>	10 simultaneous users Unlimited number of users using multicast

Alarm and Event Support	
<b>Alarm input/output</b>	Alarm input 12V DC
<b>Alarm and event</b>	Input: alarm buffer, motion detection, audio detection Output: network storage, FTP, SMTP, pre-and post alarm buffer

System	
<b>Connectors</b>	RJ-45 Ethernet 10/ 100 Base-T Reset button 2pin terminal block for DC power 6pin cable for 1 alarm input, 1 output, 1 audio line in, 1 audio line out
<b>Local storage</b>	MicroSD Card slot
<b>Software integration</b>	ONVIF 2.2 & Profile S
<b>Video management software</b>	IP Installer & video management software- ZAVIO CamGraba2.0 for viewing, recording and archiving up to 64 cameras

General	
<b>Casing</b>	IK08 vandal proof aluminum casing
<b>Power</b>	DC 12V or PoE IEEE 802.3af class 1 Power consumption: Max 5.22W PoE Power consumption: Max 5.14W
<b>Operating conditions</b>	0 ~ 50 °C (32 ~ 122 °F)
<b>Installation, management, and maintenance</b>	ZAVIO camera management tool on CD and web-based configuration. Configuration of backup and restore firmware upgrades over HTTP, firmware available at <a href="http://www.zavio.com">www.zavio.com</a>
<b>Minimum web browsing requirement</b>	Pentium 4 2.8GHz (or equivalent AMD) 256MB RAM graphic cards (or equivalent on-board graphic cards) 1G RAM Window 2000, 2003, XP, Vista or Windows 7 Mac OS Leopard 10.5 or later
<b>Dimensions (HxWxD)</b>	φ115 x 70mm (3.9" x 2.7")
<b>Weight</b>	295g (0.65lb) excl. power supply
<b>Included accessories</b>	Quick installation guide, CD (IP Surveillance Software, Intelligent IP Installer, user manual, and language packs), mounting and connector kits
<b>Certification</b>	CE, FCC, RoHS

## Part Names and Functions



## Dimensions

