

Pre-Made Security Camera Cable for Analog CCTV and HD Security Cameras

models: 25VP, 50VP, 100VP, & 150VP



These pre-made and plug-n-play Siamese cable run both power and video to CCTV security camera applications. Both ends of the video cable is pre-terminated with a male BNC connector. The power cable is pre-terminated with a male 2.1mm power plugs on one end and a female 2.1mm plug on the other.

These pre-made cables will simplify your surveillance system installation by eliminating the need to cut cables and attach connectors. These cables are available in 25, 50, 100, and 150 foot lengths.

For more information, please visit this page.

<http://www.cctvcamerapros.com/CCTV-Security-Camera-Cables-s/258.htm>

You can also find an online installation guide for pre-made security camera cables here.

<https://www.cctvcamerapros.com/Premade-Siamese-Coax-Cable-Wiring-Guide-s/1019.htm>

Models	25VP	50VP	100VP	150VP
Cable Construction				
For Video Side				
Conductor	1C*8/0.12 Pure Copper with Shield (38/0.12 CCA)			
Insulation	PE, ID: $15 \pm 0.05\text{mm}$			
Jacket	PVC, OD: $3.1 \pm 0.1\text{mm}$			
For Power Side				
Conductor	(30/0.14 BC) Red + (25/0.14 CCA) Black			
Insulation	PVC, Red: ID 1.42mm, Black: 1.25mm			
Jacket	PVC, OD: $4.1 \pm 0.1\text{mm}$			
Connectors	Iron & Copper			
Electrical Characteristic				
Impedance	50 or 75 +/- 2 Ohm			
Operating Temperature	$-20^{\circ}\text{C} (-4^{\circ}\text{F}) \sim 75^{\circ}\text{C} (167^{\circ}\text{F})$			
Reference Standard				
1. CE				
2. ROHS				
Applications				
1. Closed Circuit Television				
2. Analog CCTV Cameras, HD CCTV Cameras				

Features:

- Used for analog CCTV, AHD, HD-SDI, HD-TVI, & HDCVI Cameras
- Works with all resolutions: CIF, D1, 960H, 720p, 1080p, 2mp, 3mp, 4mp, 5mp, 8mp, 4K
- Easy to Install
- Anti-Interference Ability

Dimensions (mm)

