

<b>Model</b>	<b>DPRO-530MVF</b>	
<b>Image Sensor</b>	1/3" Sony CCD	
<b>Signal System</b>	NTSC	PAL
<b>Scanning System</b>	2:1 Interlace V: 59.94Hz.H:	2:1 Interlace V: 50Hz.H:
<b>Effective pixels(HxV)</b>	768 x 494	752 x 582
<b>Sync system</b>	Internal	
<b>Lens</b>	f=3.7mm ~ 12mm, F1.4 DC iris	
<b>IRIS Control</b>	DC Iris Driver	
<b>Auto White Balance</b>	Auto (2500°K to 9500°K)	
<b>Electronic Shutter</b>	1/60sec	1/50sec
<b>AGC</b>	On/Off	
<b>BLC</b>	ON (Center)/Off	
<b>Flickerless Mode</b>	On/Off; Fix Shutter Speed :	
<b>Digital Day/Night</b>	On/Off	
<b>Min. Illumination</b>	0.1 Lux (AGC ON)@30 IRE	
<b>S/N Ratio</b>	50dB	
<b>Voltage</b>	DC12V/AC24V±10%	
<b>Power Consumption</b>	3.0 W(MAX)	
<b>Dimensions</b>	131(L) X 131(W) X 107.5(H) mm	