

IP-MP13D Indoor Megapixel Dome Camera



Compatible with NUUO IP Camera Software

- 1/3.8" Sony Progressive CMOS Sensor
- 1280 x 960
- MPEG4 / MJPEG Video Compression
- Selectable Video Streaming
- 3.6mm Lens / F2.0
- 12V DC / PoE Support



The camera can be configured to be viewed over the Internet.

1.3 Megapixel Day & Night

Indoor Dome  Camera



SPECIFICATIONS

FC CE RoHS

Model	IP-MP13D	IP-MP13DP
Image Sensor	1/3" Sony Progressive CMOS Sensor	
Picture Elements	1280(H) x 960 (V)	
Max Aperture	F2.0	
Lens Focal Length	3.6 mm	
Angle of View	96°	
Video Compression	MPEG4 / MJPEG	
Video Streaming	Simultaneous MPEG4 and MJPEG video stream (dual stream)	
Resolution	MPEG4: VGA, QVGA, CIF, QCIF / MJPEG: 4 VGA (1280x960), VGA	
Horizontal Resolution	>700 TVL	
Frame Rate	MPEG4 30fps @ VGA / MJPEG 15fps @ 1280x960	
Image Setting	Brightness	Manual Control
	Exposure	Auto and Manual Control Mode
	Sharpness	Manual Control
	Contrast	Manual Control
	White Balance	Auto, Indoor, Outdoor, Manual Control Mode
	Digital Zoom	1x ~ 12x
	Rotation	Flip, Mirror, and 180° Rotate
Network Interface	10/100 Ethernet (RJ-45)	
Network Protocol	TCP/IP, UDP, RTP, RTSP, HTTP, ICMP, FTP, SMTP, DHCP, IGMP, and Multicast	
Password Levels	User and Administrator	
Internet Browser	Internet Explorer 6.0+	
Connectors	Ethernet	RJ45
	Audio	Built-in Mic (Optional)
Operating Temperature	32°F ~ 122°F / 0°C ~ 50°C	
Operating Humidity	10% ~ 90%, No Condensation	
Power Source	12V DC / PoE	
Regulatory	CE, FCC	
Certificate	RoHS compliant	
Dimensions W x H x L	4.08" x 4.2" x 1.7" / 103.7 x 106.7 x 44.3 mm	

*Specifications and appearance are subject to change without notice