

## **MON-7HD IP Camera & HD CCTV Camera Test Monitor** *with 7" LCD Touchscreen and up to 15 hours of battery life*



The MON-7HD is an HD CCTV and IP camera test monitor with a 7 inch LCD touch screen. This video tester is capable of displaying video from IP cameras HD CCTV cameras (HD-TVI, HD-CVI, AHD, HD-SDI), and analog CCTV cameras. The 7" LCD monitor supports 1024 x 600 resolution. This is the ultimate testing tool for installers that work with various types of security cameras.

Users can connect to IP cameras using the built-in LAN port or the built-in WiFi for a wireless connection. The monitor can power the IP camera via the POE Ethernet port (24 Watt Maximum). This monitor is also capable of powering Analog CCTV and HD security cameras (AHD, HD-TVI, HD-CVI) via the 12V-DC 2 Amp power output.

With a fully charged battery (7 hour charge time), the monitor can last up to 15 hours with normal use. An HDMI video output support 1920 x 1080 resolution. The MON-7HD also has the following features: IP address scanner, port finder and link test. All of this comes neatly packaged in a padded carrying case for ease of storage and portability.



# CCTV Camera Pros

Video Surveillance Systems for Home, Business & Government

## MON-7HD Features

Display	7 inch TFT LCD Touch screen
Screen Resolution	1024 x 600
Analog Signal Mode	NTSC / PAL (Auto Detection)
Video Input	BNC (Analog & HD BNC Cameras) 720p, 1080p, 3mp, 4mp, 5mp, 8mp / 4K Resolutions Supported
Video Input	BNC for HD CCTV Cameras (AHD, HD-TVI, HD-CVI, HD-SDI)
Power Output	12V-DC 2 Amp / POE 24 Watt Maximum / USB 5V Amp for Mobile Phone
Supported Cameras	Analog / IP (More than 40 IP Protocols and ONVIF Supported)
Battery Type	Rechargeable Lithium Ion
Battery Life	15 Hours with Normal Use (7 Hour charge time)
Storage Capacity	4GB Micro SD Card Included (Up to 32GB Supported)
Network Connectivity	LAN Port / WiFi
PTZ Controls	RS-232 / RS-422 / RS-485
Supported Baud Rates	300 / 600 / 1200 / 2400 / 4800 / 9600 / 19200 / 115200
Firmware	Update Firmware over WiFi
Flashlight	Built-in Flashlight for Dark Areas
Cable Tester	Built-in Cat-5E Cable Tester
Port Scanner	IP Port Number Scanner
Dimensions	253mm (9.96") x 176mm (6.92") x 52mm (2.04")
<b>Included Tools / Accessories:</b>	BNC Jumper Cable
	12V-DC Power Cable
	Test Monitor Strap
	Storage Bag Strap
	RS-485 Cable with Alligator Clips
	Audio Cable with Alligator Clips
	Remote UTP Cable Tester
	Power Supply / Charger
	Carrying Case

Please visit this page for more information and current pricing on the [MON-7HD IP camera and HD CCTV camera test monitor](#).