

## Portable 5.6" LCD Monitor for CCTV Testing

Model: MON-TM56



### 5.6" CCTV Testing Monitor Features:

- 5.6-inch TFT LCD monitor
- Used as a CCTV test and service monitor
- LCD screen size: 5.6 inch (116 x 87mm)
- LCD active area: 113.28 x 84.708mm
- LCD video system: A-Si TFT active matrix
- Full Color Display
- LCD module dot matrix: horizontal 320 x (RGB) x vertical 234 dots
- LCD module dot pitch: 0.118 x 0.362mm
- Overall dimension: 162 x 133 x 54mm
- Contract ratio: 200:1
- Luminosity: 250cd/m<sup>2</sup>
- Sound output: 200mW x built-in 4cm speaker 1 piece
- Input terminal: power input, video input, and audio input
- Consumption power: 12V DC/650mA, 8W maximum
- Power input: 12V DC  $\pm$ 10%
- Video input: 0.75Vp-p to 1Vp-p, pin3.5 $\Phi$
- Audio input: 50m V minimum, stereo in, pin3.5 $\Phi$
- Sound output: earphone, pin3.5 $\Phi$



- Screen display: normal/reverse switchable
- Operating temperature: 5 to 60°C
- Storage temperature: -40 to +95°C
- Maximum working hours of fully charged battery pack: 4 hours
- Battery charging time: 2 hours
- Safety approved: CE, FCC, and RoHS
- Portable monitor test kit includes a rechargeable battery pack (with charger, nylon carrying case with shoulder strap, video cable, audio cable.
- The carrying case is designed to hold the monitor and all accessories, battery pack and cables ready for field use
- This CCTV camera test kit also includes a power adapter allowing the unit to be used while the battery is being charged