

ELT-29 Corner Mount Elevator Security Camera *with wide angle 2.9mm Lens and 700TVL resolution*

The ELT-29 is an elevator security camera that uses a Sony 1/3" 520K Super HAD CCD II sensor which supports **700 TV lines** of resolution (*960H widescreen resolution*). This elevator cam has a **2.9mm wide angle lens** which that is designed to provide 100% coverage inside of small square spaces, like elevators or small rooms. The 24 infrared LEDs can fully illuminate a small room or elevator with zero light.

Although this camera is a great choice for elevator security camera applications, it is also useful in non-elevator applications as well. The ELT-29 is enclosed in **IP66** compliant waterproof housing which allows it to be used for indoor or outdoor video surveillance. Another good fit for this camera is at exterior covered door entrances where you want to get a nice wide angle of view. The metal housing makes this camera vandal-proof.



front

ELT-29 Features

Wide Angle 2.9mm Lens	Provides a 104 degree horizontal view
Resolution	700 TV Lines in color (day) + Black & White (night)
Outdoor Weather Rating	Weatherproof rating of IP66
3D-DNR (<i>Digital Noise Reduction</i>)	Includes Smart 3D-DNR
DWDR (<i>Digital Wide Dynamic Range</i>)	Includes DWDR for clear vivid pictures where strong back-lighting occurs
Video Output	Composite Video 1.0Vp / 75 Ω
Low Light	0 LUX with IRs 0.1 Lux without IR
Scanning System	2:1 Interlaced
Scanning Frequency	Horizontal 15.734 [KHz] / Vertical 59.94 [Hz] (NTSC)
S/N Ratio	More than 52 dB
Gamma Correction	0.45 Approx.
Gain Control	Automatic
Image Pick Up Device	1/3" 520K SONY super HAD II Color CCD
Effective Pixels	976 (H) x 494 (V) (NTSC) - 960H Resolution
Power Supply	DC 12V +/-10%
Power Consumption	Max 1.5 Watt
Operating Temp	Operating Temp: -10°C ~ +50°C / 14°F to 122°F
Dimensions (inches + mm)	Height: 42.3mm Width: 190mm Length: 140mm
Weight	Weight: 330 Grams

