

## GV-COM V3



The GV-COM V3 adds one RS-485 port to your computer through a USB connector. Using the GV-COM V3, you can connect your computer to PTZ Cameras, GV-Data Capture Box or any other RS-485 devices.

Specifications		
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008
	64-bit	Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 / Server 2012 R2
Serial Interface	RS-485	RS-485+, RS-485-
	Serial Line Protection	8 KV ESD for All Signals
USB	Compliance	USB 2.0 Backward Compatible
	Speed	Full speed 12 Mbps
Communication Parameters	Parity	None, Even, Odd
	Data Bit	7, 8
	Stop Bit	1, 2
	Flow Control	RTS / CTS, XON / XOFF
	Speed	600 bps to 115,200 bps
Environmental Conditions	Operation Temperature	0~50°C / 32~122°F
	Humidity	5%~95% (Non-Condensing)
Dimensions (W x H x D)		325 x 18 x 9 mm / 12.8 x 0.7 x 0.35 in
Weight		22.3 g / 0.049 lb
Installation Guide		<a href="#">GV-COM V3</a>

**Note:** All specifications are subject to change without notice.