

GV-SDI to HDMI



The GV-SDI to HDMI is a converter from SDI to HDMI and provides two SDI video outputs with the repeater function.

Feature

- Auto 3G/HD/SD-SDI detection
- The converter is Plug-and-Play
- Dual outputs are available (SDI & HDMI)
- One 3G-SDI source to two 3G-SDI device

SPECIFICATIONS

Camera		
Support Video Resolution	3G	1080p60 / 59.94 / 50
	HD	1080p30 / 29.97 / 25
		1080i60 / 59.94 / 50
SD	625i (PAL) / 525i (NTSC)	
SDI format	3G-SDI (SMPTE 424M) HD-SDI (SMPTE 292M) SD-SDI (SMPTE 259M)	
Re-clock Function	Yes (Dip Switch)	
Coaxial Cable Type	RG6/RG59 (75 ohm)	
Cable Equalization	3G	140 m of RG6 100 m of RG59
	HD	200 m of RG6 140 m of RG59
		SD
Connectors		
Input	1 x BNC (SDI)	
Output	1 x HDMI 2 x BNC (SDI)	
BNC Connector	3G 75 ohm inter-locked socket	
HDMI Connector	Type A (19-pin female)	
DIP Switch	3-pin (Re-clock / LED mode / NA)	
General		
Housing	SECC	
Dimensions (L x W x H)	104 mm x 63.3 mm x 26 mm / 4.09 in x 2.49 in x 4.49 in	
Power Source	Power Adapter: AC 100 ~ 240 V/DC (+6 ~ 15 V)	
Operation Temperature	0 ~ 50 °C / 32 ~ 114 °F	

[Installation Guide](#)

Note: Specifications are subject to change without notice.