

GV-IO Box 16 Ports



The GV-IO Box 16 provides 16 inputs and 16 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

| Specifications | | |
|--------------------------|-------------------|------------------------------------------------------|
| OS Supported | 32-bit | Windows XP / Vista / 7 / 8 / Server 2008 |
| | 64-bit | Windows 7 / 8 / Server 2008 R2 / Server 2012 |
| Compatible S/W | | GV-System version 8.2 or above |
| Input | Input | 16 |
| | Input Signal | Dry Contact Wet Contact, 9-30V AC/DC |
| Communication | Relay Output | 16 |
| | Relay Status | Normal open |
| | Relay Capacitance | USB Connection |
| RS-232 Connection | | 125 / 250 VAC, 3A 30 VDC, 3A |
| Ethernet | | RJ-45, 10/100 Mbps (Optional) |
| DC IN | | DC 12V, 1A |
| Address | | 0-9, A-F |
| Terminal Resistance | | 120 ohm |
| Environmental Conditions | | 0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing) |
| Dimensions (W x H x D) | | 180 x 27 x 183 (mm) / 7.09 x 1.06 x 7.2 (in) |
| Installation Guide | | GV-IO Box 16 |

Note: All specifications are subject to change without notice.

