

## MON-LCD-19BNC BNC Surveillance Monitor

*19-inch LED 1080p HD monitor with BNC Inputs that support AHD, HD-TVI, HDCVI, and CVBS / Analog security cameras.*



The MON-LCD-19BNC is a 19-inch LED video surveillance monitor with a BNC input connector to natively support Analog CCTV (CVBS), HD-TVI, HDCVI, and AHD security cameras. These BNC monitors also have a looping BNC output that can be used to run the camera's video to a second device, such as a video surveillance DVR.

A desk stand is included, and the monitor is also compatible with VESA 100 wall mounts. These surveillance monitors support an input of up to 1920 x 1080 (1080p) resolution. For global support, the MON-LCD-19BNC supports both the NTSC and PAL video resolution. The BNC inputs on the monitor detect the type of video standard being used and automatically switch to support it.

Visit this page for more information on this [19" BNC monitor](#). Additional [BNC monitors](#) here.

## BNC Monitor Connectors





# CCTV Camera Pros

Video Surveillance Systems for Home, Business & Government

## MON-LCD-19BNC Features

Diagonal Screen Dimension	19 Inches
Viewable Area	14.81" x 11.87" / 376.1mm x 301.4mm
LED Type	RGB (Red / Green / Blue)
Pixel Pitch	0.294mm
Screen Maximum Resolution	1280 x 1024
Supported Input Resolutions	720 x 400 / 640 x 480 / 800 x 600 / 1024 x 768 / 1280 x 1024 / 1360 x 768 / 1680 x 1050 / 1920 x 1080
Refresh Rate	60 / 70 / 75Hz – Depending on Resolution
Color Depth	24 bits / 16.7 Million Colors
Brightness	250 cd/M <sup>2</sup>
Auto Adjust	Yes
Monitor Aspect Ratio	4:3
Display Aspect Ratio	OSD – Selectable 16:9 or 4:3
Horizontal TV Lines (BNC Source)	600 TVL
Contrast Ratio	1000:1
Response Time	5ms
View Angle H/V	178° / 178°
Digital Video Inputs	HDMI up to 1920 x 1080
Port Inputs	HDMI / VGA / BNC In / HD In (AHD/HD-TVI/HDCVI/CVBS) / USB (Updates)
Port Outputs	HD BNC Out (AHD/HD-TVI/HDCVI/CVBS)
Audio Input (Stereo)	3.5mm
Audio Output (Stereo)	3.5mm
Speakers	8 Ω 3 Watt per Channel
Filter Type	3D Comb Filter
De-Interlace / Noise Reduction	3D De-Interlace
OSD Languages	English / Spanish / German / Chinese / French / Italian
Monitor Housing Dimensions	16.4" x 14.37" x 2.38" / 418.4mm x 365.1mm x 60.6mm (Without Stand)
Monitor + Stand Dimensions	16.4" x 16.2" x 7" / 418.4mm x 412.1mm x 180mm (With Stand)
Case / Stand Material	Plastic
VESA Mounting Pattern	100 x 100 – Centered on Monitor Body
Base / Stand Included	Yes
Net Weight	4.28kg / 9.43lbs
Gross Weight	4.60kg / 10.14lbs
Power	< 30 Watts
Power Input	100 ~ 240VAC
Operating Temperature	32° ~ 104°F / 0° ~ 40°C
Storage Temperature	-4° ~ 140°F / -20°C ~ 60°C
Operating Humidity	10 ~ 85%
Certifications	CE / FCC / UL



For information relating to video surveillance, please contact us, via email at [info@cctvcamerapros.net](mailto:info@cctvcamerapros.net), or by phone at 561-433-8488 / 888-849-2288; or visit our Website: [www.cctvcamerapros.com](http://www.cctvcamerapros.com)