

User Manual

Bullet Network Camera

F34-875070-000A 875PRO A.1

Safety Notice

- Make sure the supplied voltage meets the power consumption requirements of the camera before powering the camera on. Incorrect voltage may cause damage to the camera.
- The camera should be protected from water and moisture, excessive heat, direct sunlight and cold.
- The installation should be made by a qualified service person and should conform to all local codes.
- Unplug the camera during lightning storms or when unused for long period of time.

Table of Contents

1. Overview	5
1.1 Package Contents	5
1.2 Hardware Overview.....	5
1.2.1 Part Names	5
1.2.2 Connectors	6
1.2.3 Dimensions	7
1.3 Specifications.....	8
2. Installation	9
2.1 Inserting Memory Card.....	9
2.2 Mounting the Camera	9
2.3 Adjusting the View and Focus	10
3. Network Connection and Configuration	12
3.1 Network Connection Types	12
3.2 Accessing the Camera for the First Time.....	14
3.3 Using "IP Finder" to Manage Cameras	16
3.3.1 Installing IP Finder.....	16
3.3.2 Using IP Finder	16
4. Using Web-based Control Utility	19
4.1 Overview.....	19
4.1.1 Main Screen	19
4.1.2 Setup Menu.....	20
4.1.3 Applying Settings.....	20
4.2 Image Settings	20
4.2.1 Codec	20
4.2.2 Exposure	23
4.2.3 White Balance	25
4.2.4 Basic Setting	26
4.2.5 Smart Encoding	27
4.2.6 Smart Focus.....	28
4.2.7 Privacy Zone	28
4.2.8 ePTZ	29

4.3 Network	30
4.3.1 Basic.....	30
4.3.2 FTP.....	31
4.3.3 SMTP	32
4.3.4 NTP	33
4.3.5 RTSP	33
4.3.6 ONVIF	34
4.4 System	35
4.4.1 Date and Time.....	35
4.4.2 Time Stamp	36
4.4.3 Firmware	36
4.4.4 User Management	38
4.4.5 Language	39
4.4.6 Log.....	39
4.4.7 Audio	40
4.5 Event.....	41
4.5.1 Motion Detection.....	41
4.5.2 External Alarms	42
4.5.3 Blur Detection	43
4.5.4 Audio Detection	44
4.5.5 Ethernet Detection	45
4.5.6 Event Management.....	45
4.6 Recording	46
4.6.1 Settings – Video Clip	46
4.6.2 Settings – FTP	47
4.6.3 Settings – SMTP	48
4.6.4 SD Card Storage Format Selection	49
4.6.5 Period Setting.....	50

1. Overview


1.1 Package Contents

The package includes these items:


■ Bullet Network Camera	x1
■ CD-ROM (User manual and IP Finder utility)	x1
■ Quick Start Guide	x1
■ Guide Pattern	x1
■ Insulation caps	x3
■ Self-tapping Screw (TP4 x 31mm)	x3
■ Plastic Anchor	x3
■ RJ-45 Female / Female Coupler	x1
■ 2-pin Screw Terminal Block	x1

1.2 Hardware Overview

1.2.1 Part Names




1. **Mounting Bracket Assembly:** To attach to mounting surface and adjust the camera at different angles.
2. **Sunshield:** Minimize the effects of rain and sunlight on image quality.
3. **Rear cap:** Remove it to expose the camera connectors.
4. **Front cap:** Remove it to expose the lens and reset controls.



5. **microSD/SDHC Card Slot:** Insert a microSD/SDHC card to the slot for recording and storage.
6. **Far/Near Control:** Loosen to control to adjust the picture sharpness.
7. **Tele/Wide Control:** Loosen the control to adjust the image view.
8. **Reset:** Use an appropriate tool to press the button to reset the camera. Hold for 5 seconds to reboot camera. Hold longer than 5 seconds to load default settings


1.2.2 Connectors



1. **Power In:** Connect to DC12V/AC 24V power supply. If using DC 12V power supply, make sure to connect the power connector to correct ports (Red+/Black-). If you are to use power from Ethernet connection, this connector is not used when the power is provided by PoE.
2. **RJ-45 (Ethernet/PoE):** Connect to the LAN port of a standard 10Base/100Base-TX device, e.g., hub, switch or router. If you are going to use PoE function, connect to a PoE-capable network device. Power will be supplied through the Ethernet cable.
3. **BNC:** Connect to composite video in connector of a monitor.
4. **Audio Out:** Connect to an external speaker.
5. **Audio In:** Connect to an external microphone
6. **GND:** Ground (electricity) in electrical circuits.

7. **Alarm IN 1/2:** Connect to device that responds to alarm signals.
8. **Alarm Out:** Connect to device that triggers alarm signals.

1.2.3 Dimensions



1.3 Specifications

Description	Bullet Network Camera
Image System	
Image Sensor	1/2.7" 2MP image sensor optimized for low-light performance
Image Compression Method	Triple Streaming : H.264 / MPEG4 / Motion JPEG
Maximum Frame rate vs. Resolution	30 fps (NTSC) and 25 fps (PAL) in 2MP Full HD 1080p (1920x1080)
Lens	Built-in Mechanical IR Cut Filter varifocal lens f=3~9mm, F1.2 (Mega pixel lens)
View Angle	H: 93°(Wide)~31.7°(Tele)/V:68.4°(Wide)~23.8°(Tele)
Electric	
Shutter Time	Range from 1/10000s to 1/3.75s selectable (60Hz); Range from 1/10000s to 1/3.125s selectable (50Hz)
Audio	Two-way Mono Audio, Full-duplex, G.711 PCM 8kHz
Alarm	External input
RS-485	Reserved
Day/Night Mode	Mechanical (ICR) D/N control: Auto Mode
Minimum Illumination	IR LED OFF: 0.08 Lux @30IRE; 0.20Lux @50IRE (shutter speed: 1/15sec) IR LED ON: 0 lux
IR LED	IR LED 24 pcs (850nm)
IR Distance	25 meters (82 ft.)
IR Turn On Status	Under 10 lux by auto control
LED Life	More than 10,000 hours (50°C)
Video Port	BNC X1, 1.0Vp-p, 75Ω
Video Output	NTSC: 720 X 480 @30fps; PAL: 720 X 576 @25fps
Image Enhancement	AWB, AES, AGC Exposure Mode: Auto/Manual White Balance: Auto/Manual Backlight Compensation: 5x5 zones selectable Sharpness, Saturation, Brightness, Contrast: 255 level sensitivity
Feature Brief	
Digital WDR	Yes; 5 level sensitivity
Privacy Zone	Yes; customized threshold privacy zone
Intelligent Video	Audio detection / Blur detection /Ethernet Detection/ Smart Encoding/ Smart Focus/ e-PTZ/ Event Management
Alarm Detection	Motion Detection: 5 x 5 zones, 5 level sensitivity or customized threshold Audio Detection: 5 level sensitivity or customized threshold Blur Detection: customized threshold External Input
Alarm Event	File upload via FTP, SMTP and SD Card Notification via email, HTTP and TCP External output activation Video and audio recording to SD Card
Image Orientation	Mirror, Flip
Bit Rate Mode	Primary stream bit rate control: CBR/VBR
Local Storage	
Memory Card	Micro SD/ Micro SDHC Card up to 32 GB
SD Card Overwrite	Yes
SD Card Store Category	Alarm / Motion / Schedule/ Un-interrupt recording
Power supply	
Power Requirement	DC 12V & AC 24V ± 10% / PoE(IEEE 802.3af)
Power Connector	Screwless Terminal Block
Power Consumption (Max.)	8W.
Environment	
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122 °F)
Operating Humidity	10~ 90% RH
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140 °F)
Regulatory	CE, FCC, RoHS

Network	
Ethernet	10Base-T/100Base-TX Ethernet connection for LAN / WAN, RJ-45
Internet Protocol	IPv4, TCP/IP, UDP, HTTP, SMTP, DNS, DHCP, NTP, FTP, RTP,RTSP, ICMP, UPnP
Browser	IE browser 6.0 or above
I/O connector	
Alarm Port	Terminal Block 2 in / 1 out
Audio In / Out port	3.5mm Phone Jack 1 in / 1 out
RS-485 Port	Terminal Block
Reset	Within 5 sec for rebooting system; more than 5 sec for loading default
Mechanism	
Dimensions(ΦxH)	300mm x 88mm x 86 mm (11.79inch x 3.47inch x 3.39inch)
Weight	995g (2.2 lb.)
Protection Class	IP67
Accessory	
Mount Type	Easily adjustable 3-axis and cable-concealed bracket with standard package Corner mount: Adapter required Pole mount: Adapter required

2. Installation



Warning

The front and rear cap should NOT be removed over 30 minutes during installation. Otherwise, the desiccant will absorb too much moisture and thus cause vapor.

2.1 Inserting Memory Card


1. Loosen the two sunshield fixing screws and remove the sunshield.
2. Loosen the three screws to remove the mounting bracket assembly.
3. Loosen the three screws to remove the rear cap from the main body.
4. Insert your microSD/SDHC card into the slot.



Caution

When inserting the memory card, make sure not to disconnect any cables attached to the camera.

5. Re-assembly the rear cap and the mounting bracket assembly.



2.2 Mounting the Camera


1. Drill mounting holes and insert anchors.

In desired location, use the supplied Guide Pattern to drill three 5mm mounting holes. Then insert the supplied anchors into the holes.

2. Pass all the signal cables through the hole for the cables.

Optionally connect a video monitor to the BNC connector if you want to perform focus/zoom adjustments during the installation.


3. For static electricity protection, ensure that the rubber pad is placed inside the mounting bracket base.
4. Place the three provided insulation caps onto the three tapping screws. Insert the screws to the screw holes on the camera bracket, and then tighten the screws to the anchors to attach the camera .



2.3 Adjusting the View and Focus

Refer to the figure below, loosen the screws as needed to adjust the camera to desired angel.

1. Loosen the screw to rotate the pipe segment.
2. Loosen the screw and the opposite one to tilt the bracket base.
3. Loosen the screw and the opposite one to rotate the bracket base.



4. Rotate the front cap to remove it from the main body.



Caution


- Two desiccant packs are already placed near the lens. The desiccant pack prevents fogging on the inside of the lens due to any moisture. Make adjustments within 30 minutes or the desiccant pack may absorb too much moisture and become ineffective.
 - Desiccant packs that have absorbed too much moisture need to be replaced or reactivated.
 - When lens adjustments are complete, reattach the camera cover and sunshield.
5. Unlock the Near/Far and Wide/Tele screws to adjust the sharpness and view. After the adjustment, lock the controls.
 6. Re-install the front cap to the main body.



Caution

Securely fasten the front cap on the camera in order to avoid water damage. The gap between the camera body and the front cap should be less than 1mm.

7. Re-install the sunshield by screwing the two screws.



3. Network Connection and Configuration

3.1 Network Connection Types


There are many different ways that you can connect the camera to your network, depending on your applications requirements. You should always set the camera's network settings according to your network configurations. The following diagrams depict some typical applications with guidelines on network settings. For more information on network settings, always consult with your network administrator or ISP as required.

Type 1— Direct Connection to a PC

Directly connect the camera to a PC using a standard Ethernet cable.



To extend the connection length, you should use a RJ-45 female/female coupler to connect two Ethernet cables together.



Note

The LAN port of the camera supports auto MDI/MDIX (Medium dependent interface crossover) so there is no need to use cross-over cable.

To access the camera, the PC must be on the same network as the camera. The default IP address of the camera is a static one (192.168.1.30). Configure your PC's IP address as 192.168.1. X (where X is a number between 2 to 254, excluding 30 and subnet mask as 255.255.255.0, and then your PC should be able to access the camera.

Type 2: Connecting Camera(s) to a Local Area Network (LAN)

To add the camera(s) to an existing LAN, just connect the camera(s) to the hub or switch on your network. If you want to provide the camera power via the Ethernet connection, a PoE-enabled hub/switch is required.




Note

The LAN port of the camera supports auto MDI/MDIX (Medium dependent interface crossover) so there is no need for an uplink port or the use of a cross-over cable.

Assign an IP address to your camera following your network IP allocation policy. You can manually specify the IP address or allocate the IP address automatically using a DHCP server, if available on your network.

Then, you can monitor and manage the camera via a web browser from a local PC.




Router/Switch/Hub

Type 3: Remote Connection via the Internet

If the network where the camera resides is connected to the Internet, you can also provide remote access to your camera over the Internet.

Typically a broadband router has a built-in DHCP function to assign a local IP address to your camera. You can alternatively assign a fixed IP address to the camera to prevent it from frequently changing.



To access the camera from a local PC, simply use the local IP address of the camera.

To enable remote access, you must configure your router/firewall to forward an incoming request to that fixed local IP address of the camera. Therefore, when an external host sends a request to access your camera, the request will first reach the router's external IP address and then be forwarded to the local IP address of the camera.

Port forwarding is based on the service you want to provide. For example, forward HTTP port to enable remote web access to your camera, or RTSP port to enable access to video/audio streams from the camera.

If your camera is configured to use a non-standard HTTP port, then you have to forward that port accordingly.

3.2 Accessing the Camera for the First Time

The camera comes with a web-based setup utility, allowing you to view the video of the camera and configure the camera for optimal use in your environment.

To access the camera's web-based control utility, you need a PC that meets the following requirements:

- **Operating System:** Windows Vista® or XP
- **Browser:** Internet Explorer Version 6.0 or later
- **CPU:** Intel Pentium 4.2 GHz or higher
- **RAM:** 512 MB or more

Then take the following steps to connect your PC to the camera.

Step 1: Make the connection


For initial setup purposes, connect one end of an Ethernet cable to the RJ45 connector of the camera and the other end to the LAN port on your PC.

Step 2: Configure your PC's IP address

The camera uses a default IP address of 192.168.1.30 and subnet mask of 255.255.255.0. To have your PC on the same network with the camera, configure your PC's IP settings as below:

- **IP address:** 192.168.1. X, where X is a number between 2 to 254, excluding 30.
- **Subnet mask:** 255.255.255.0.


Ignore all other settings and click **OK**.



Step 3: Verify the connection between the PC and the IP Cam

1. Launch the Command Prompt by clicking the **Start** menu, **Programs**, **Accessories** and then **Command Prompt**.
2. At the prompt window, type `ping x.x.x.x`, where x.x.x.x is the IP address of the camera (the default is 192.168.1.30).

If the message of **"Reply from..."** appears, it means the connection is established.



Step 4: Access the camera from IE browser


Open the IE browser and enter the IP address of the camera in the URL field. The default is 192.168.1.30.



When prompted to login, enter the user name and the password. (The defaults: admin, 1234). Note that the password is case-sensitive.



Upon successful login, you will see the live view screen shown as the example below:



3.3 Using “IP Finder” to Manage Cameras

IP Finder is a management tool included on the product CD. It is designed to manage your network cameras on the LAN. It can help find multiple network cameras, set IP addresses, show connection status and manage firmware upgrades.

3.3.1 Installing IP Finder

Before proceeding, make sure your operating system is Windows Vista or Windows XP.


To install the software, simply locate and double-click the **IP Finder** setup file on the provided CD. Then follow the on-screen prompts to proceed.

3.3.2 Using IP Finder

To launch IP Finder, double-click the **IP Finder** shortcut on the desktop or click **Start > Programs > IP Finder > IP Finder**.


After you launch **IP Finder**, it will search for all the available cameras on the same network. Click the plus sign next to “**All Devices**” to expand the menu and display all the found cameras.

Clicking a target camera will show the live view (if available) and the detailed information of the camera, including the MAC address. Each camera comes with a unique MAC address, which is indicated on the product label. It helps identify which camera is currently accessed, particularly when multiple cameras are connected on your network.



The **Tool** menu of the **IP Finder** allows you to perform these tasks:


- **Search Network:** This option allows you to search the cameras on the network.
- **Set Master ID and Password:** Allows you to set a master ID and password for managing the cameras with IP Finder.
- **Management Tool:** Allows you to restart the camera, update firmware, reset all of the camera settings to default (except network settings) and reset all of the camera parameters to default.



3. Network Connection and Configuration


For an individual camera, right-click the camera and a menu will provide these options:

- **Go to Presentation URL:** Launch IE browser to access the web-based utility of the camera.
- **Set Device ID and Password:** Set the login ID and password for managing the camera with IP Finder.



A small dialog box titled "Enter ID and Password". It contains two text input fields: "ID:" and "Password:". Below the fields is an "OK" button.

- **Network Information:** Allows you to configure the camera's network settings.




A dialog box titled "Network Information". It has two radio buttons: "Obtain IP Address From DHCP" and "Manual Setup". The "Manual Setup" option is selected. Below the radio buttons are five text input fields: "IP Address:" (192.168.1.30), "Subnet Mask:" (255.255.255.0), "Default Gateway:" (192.168.1.1), "DNS:" (168.95.1.1), and "HTTP Port:" (80). At the bottom are "OK" and "CANCEL" buttons.

4. Using Web-based Control Utility

4.1 Overview

4.1.1 Main Screen

After you login to the camera's web-based control utility, you will first see the live view screen of the camera. The screen is like the picture below:



The live view screen of the utility provides these options:

- **Snapshot:** Pressing this button takes a snapshot of the current live view screen.
- **Live:** Pressing this button displays the live view of the camera.
- **Setup:** Pressing this button allows you to access the setup page.
- **Camera name:** Displays the name of the camera.
- **Recording Indicator:** Turns red when the recording is proceeding.
- **Alarm Indicator:** Appears when an alarm is triggered.
- **Live view video:** Shows the live view of the camera.

Note that the accessibility to the options varies according to the login account.

- **Viewer:** Allowed to view only the live view screen. Access to other options is restricted.
- **Administrator:** Can access all the options on the live view page and make configurations on the setup pages.

4.1.2 Setup Menu

The **Setup** options are categorized into five groups: **Image**, **Network**, **System**, **Event** and **Recording**. Clicking the name will expand its sub-menu. See the ensuing sections for more information.

4.1.3 Applying Settings

Each configuration page provides a **Save** button. Settings are applied right after you press the **Save** button. And the browser will refresh to load the latest setting or otherwise pop up the **"Save OK"** message to indicate that settings have been applied.

4.2 Image Settings

4.2.1 Codec

The Codec page allows you to configure the video streams for the camera. You can optionally configure a secondary or third stream to a resolution as required by your third-party device or software.

Basic Setting	
Camera Name:	IPNetCam
Primary Stream:	Codec: H264 Resolution: 1080P (1920x1080) Bit Rate: 8000 kbps (500~8000) Frame Rate: 12.5 FPS
Secondary Stream:	Codec: OFF Resolution: ... Bit Rate: 4000 Kbps (500~4000) Frame Rate: 12.5 FPS
Third Stream:	Codec: OFF Resolution: ...
Mirror:	OFF
Rate Control:	VBR
TV Out Stream	ON
<input type="button" value="Save"/>	

Camera Name Settings

- Enter a descriptive name of the camera. Note that if you want to make the camera ONVIF compliant (see **Network > ONVIF**), no space is allowed in the camera name.

H.264 Codec Settings

- **Resolution:** Choose a resolution for the video. Choices include 1080p, SXVGA, 720p, XGA, SVGA, D1, 2CIF, VGA, and CIF.
- **Bit Rate:** According to your bandwidth, specify a value for data transmission rate (kbps). Higher value gets higher video quality but consumes more bandwidth.
- **Frame Rate:** Choose the intended frame rate, i.e., the number of frames to transmit per second.

MPEG4 Codec Setting

- **Resolution:** Choose a resolution for the video. Choices include 1080p, SXVGA, 720p, XGA, SVGA, D1, 2CIF, VGA, and CIF.
- **Bit Rate:** According to your bandwidth, specify a value for data transmission rate (kbps). Higher value gets higher video quality but consumes more bandwidth.
- **Frame Rate:** Choose the intended frame rate, i.e., the number of frames to transmit per second.

MJPEG Codec Settings

- **Resolution:** Choose a resolution for the video. Choices include 1080P, SXVGA, 720P, XGA, SVGA and D1.
- **Quality:** Set the image's quality as High, Normal or Low.
- **Frame Rate:** Choose the intended frame rate, i.e., the number of frames to transmit per second.



1. Live View uses the MJPEG codec. If no streaming is using MJPEG, it will result in no video for Live View.

Codec

No JPEG Codec! Please choose a suitable codec mode on Setup->Image->Codec page.

2. If MJPEG is selected for both the primary stream and the third stream, Live View will always display video using the third stream codec settings.

Refer to the table below for selectable codec types for each streaming:

Streaming Combination					
Primary		Secondary		Third	
Codec	Resolution	Codec	Resolution	Codec	Resolution
MJPEG	1080P	OFF	N/A	OFF	N/A
		H264 MPEG4	D1 VGA 2CIF CIF		
	SXVGA 720P XGA SVGA D1	OFF	N/A	OFF	N/A
				MJPEG	VGA CIF
		H264 MPEG4	D1 VGA 2CIF CIF	OFF	N/A
				MJPEG	VGA CIF
H264 MPEG4	1080P	OFF	N/A	OFF	N/A
				MJPEG	VGA CIF
	SXVGA 720P XGA SVGA D1	OFF	N/A	OFF	N/A
				MJPEG	VGA CIF
		H264 MPEG4	D1 VGA 2CIF CIF	OFF	N/A
				MJPEG	VGA CIF

Mirror Settings

This option allows you to mirror or flip the video image if required.

- **OFF:** Turns off this function.
- **HORIZONTAL:** Flips the images horizontally.
- **VERTICAL:** Flips the images vertically.
- **BOTH:** Flips the images vertically and horizontally.

Rate Control

Choose a bit rate control to manage your bandwidth usage.

- **Variable Bit Rate (VBR):** VBR keeps the video stream quality as constant as possible by varying bit rate. This mode ensures high quality image for motion scene and is often selected when image quality demands priority. However, this mode requires more bandwidth in order to vary the bit rate.

- **Constant Bit Rate (CBR):** CBR maintains a specific and constant bit rate by varying the stream quality. With CBR, streaming is smooth and network throughput is stable for any scene. This mode is typically used with a limited bandwidth environment.

TV Output Stream

Turn on this option if you connect an analog monitor to the camera's **Video** connector for video output.

4.2.2 Exposure

The **Exposure** page allows you to configure the **Exposure Mode** and **Backlight Compensation** settings according to the light conditions of the camera.

Exposure Mode

Exposure Mode	
<input checked="" type="radio"/> Auto Exposure	
Method	Center weighted ▾
EV	0 ▾
Max Exposure	1/3.125 ▾
Min Exposure	Unlimited ▾
Sensitivity	10 ▾
Max. Gain	Default ▾
<input type="radio"/> Manual Exposure	
Exposure Time	1/ 30.00 Sec (1/3.75~1/10000)
Gain	0 ▾

Auto Exposure Settings

- **Method:** Select which area of the image will be used to measure the amount of light to achieve best exposure.
 - **Center Weighted:** Exposure metering is averaged over the entire frame but emphasis is placed on the central area.
 - **Object Targeted:** This option meters the exposure based on the targets you specify. When this option is selected, define your target by clicking squares displayed on the image and then press **Save Spot Window** to save the setting.
- **EV:** In a scene with predominantly light or dark areas, the image will be underexposed or overexposed, causing an image to be too dark or bright. In such situations, you can adjust a compensation value to optimize the exposure. Decrease the value if images appear too light (overexposed). Increase the value if images are too dark (underexposed).
- **Max/Min. Exp:** Select the maximum / minimum exposure time according to the light source. The selectable value will change according to the frequency setting under **Image > Basic Settings**.


- **Sensitivity:** Select how sensitive the camera reacts to the light. A higher value enables the camera to be more sensitive to the light conditions and adjust the exposure in the shortest time interval.
- **Max Gain:** Specify the maximum amount of amplification applied to the image. A high level of gain allows images to be viewable in very low light, but will increase the image noise.

Manual Exposure Settings

- **Exposure Time:** Enter a desired exposure time.
- **Gain:** Select a gain value from 0 to 16. A high level of gain allows images to be viewable in very low light, but will increase image noise.

BLC (Backlight Compensation)

The **Backlight Compensation** function allows you to provide the optimal exposure of subjects under back light circumstances.



- **OFF/ON:** Choose to enable or disable the BLC function.
- **BLC area setting:** BLC area refers to the dark area where more details are expected. Define your BLC area by clicking squares displayed on the screen and then press Save BLC Window to save the setting.

Digital Wide Dynamic Range




When there are both very bright and very dark areas simultaneously in the field of view, you can enable Digital Wide Dynamic Range (WDR) function. It optimizes an image to ensure that dark areas are more visible while retaining details in bright areas.

- **Level:** Depending on the contrast/dynamic range of a scene, you can select different level of WDR. Higher level of WDR suits for higher contrast/dynamic scene. If you select **Auto** mode, the camera will automatically adjust the WDR level by itself depending on the light of the scene.

4.2.3 White Balance

White Balance



White Balance Mode

☒ Auto White Balance

Sensitivity

☐ Manual White Balance

R Gain (0.4~4.0)

G Gain (0.4~4.0)

B Gain (0.4~4.0)


Select a white balance mode according to external light condition for the best color temperature.

- Auto White Balance:** Use this option when there is no special lighting in the environment. The camera will automatically adjust the color temperature according to the light conditions and the sensitivity you specify. The higher the sensitivity, the faster the adjustment. If the lighting conditions change frequently, select a lower sensitivity to prevent the camera from frequently changing white balance.
- Manual White Balance:** With any special light in the environment, you can use this option to manually adjust the red, green and blue channels, which are mostly affected by the special light. For example, if red color is too bright, then you should lower the R Gain value.

4.2.4 Basic Setting

The **Basic Setting** allows you to specify a frequency and adjust the basic image settings to optimize your video image.

Basic Settings



Basic Setting

Frequency	<input checked="" type="radio"/> 50 Hz <input type="radio"/> 60Hz
TV System	<input type="radio"/> NTSC <input checked="" type="radio"/> PAL
Brightness	< 128 > (0-255)
Contrast	< 128 > (0-255)
Saturation	< 128 > (0-255)
Sharpness	< 128 > (0-255)

Default All Image Parameters.

Save

- **Frequency:** Select an appropriate frequency to reduce the flicker on the image. "50 Hz" and "60 Hz" are provided. Frequencies settings will affect the **Max. Exposure** and **Min. Exposure** settings under **Image > Exposure**.
- **TV System:** Displays the current video standard: NTSC or PAL. This setting cannot be changed via web interface.
- **Brightness:** Adjust the image brightness level.
- **Contrast:** Adjust the image contrast level.
- **Saturation:** Adjust the image saturation level.
- **Sharpness:** Adjust the image sharpness level.
- **Default All Image parameters:** Pressing this button will restore all the image settings to the defaults.

4.2.5 Smart Encoding


On the **Smart Encoding** page you can specify a specific region of the video as more important, i.e., a region of interest (ROI). When a ROI is specified, the camera will assign a higher number of bits to the ROI area to deliver better video quality than non-ROI areas.



Note

The Smart Encoding function is only available when H.264 is selected for one of the streams.

Smart Encoding



Save Window

Basic Setting

Smart Encoding	Mode	Fixed ROI ▼
	Priority	Level1 ▼

Save


Basic Setting

To define a smart encoding area, click and drag your mouse on the image to define the region of interest and click **Save Window** to save the region. Click anywhere on the image to cancel the current defined area.

- **Mode:** Select **Fixed ROI** to enable smart encoding function.
- **Priority:** Select a priority level for the ROI.

4.2.6 Smart Focus

In addition to observing the live view image to see if focus is achieved, you can also enable **Smart Focus** to help you verify if focus is locked. If this function is enabled, whenever focus is achieved, the focus window turns green.



Basic Settings

To focus on a desired subject using the Smart Focus function:


1. Click on the subject that you want to focus on and then click **Save Window**.
2. Check the **Smart Focus Enabled** box. This will turn the smart focus indicator to red.
3. Use the focal length and focus controls to optimize the focus. When focus is achieved, the indicator turns green.

4.2.7 Privacy Zone

Privacy Zone allows you to mask sensitive areas of the image for privacy protection. If enabled, it will mask the live view and the recorded video clips/JPEG files.

To turn on the privacy zone function:

1. Click and drag your mouse on the image to define the region to be masked and then click **Save Window**.
2. Select **ON** to enable **Privacy Zone**. This will turn the masked area to black.




4.2.8 ePTZ

Using the ePTZ function, you can use the pan, tilt and zoom controls to steer the camera to a desired position and focus on desired close-up areas, without moving the camera physically.

To use the ePTZ function:

1. On the **Image > Codec** page, make sure one of the streams are configured to use **MJPEG** codec and **D1** resolution.



2. On the main screen, a **PTZ** button will appear. After you click the **ePTZ** button, an ePTZ control panel will appear where you can click the corresponding indicators to perform desired operations:
 - **To zoom in/out:** Click the +/- indicator repeatedly to zoom in/out the live view image.
 - **To pan left/right:** Click the left/right indicator to pan the viewing area. The pan function does not work if the video is not zoomed-in (no zoom status).
 - **To tilt up/down:** Click the up/down indicator to tilt the viewing area. The tilt function does not work if the video is not zoomed-in (no zoom status).
 - **To preset to home:** Click the home indicator and the image will return to the original view.



4.3 Network

4.3.1 Basic

Basic		
Basic Setting		
<input type="checkbox"/> DHCP		
IP Address:	<input type="text" value="192.168.1.30"/>	
Subnet Mask:	<input type="text" value="255.255.255.0"/>	
Default Gateway:	<input type="text" value="192.168.1.1"/>	
DNS:	<input type="text" value="168.95.1.1"/>	
HTTP Port:	<input type="text" value="80"/>	[80, 1025~65535]
MAC:	00:0b:67:00:d9:e5	
<input type="button" value="Save"/>		

- **DHCP:** If there is a DHCP server on the network and you enable this option, the server will automatically assign an IP address and related information to the camera.



Note

If there is no DHCP server on your network or you prefer to manually assign an IP address to the camera, leave the DHCP checkbox blank.

- **IP Address & Subnet Mask:** If the DHCP function is not enabled, you have to assign an IP address with the subnet mask to the camera.
- **Default Gateway:** Enter the IP address of the gateway if required. Please contact your network administrator whether you need to set up the gateway.
- **DNS:** Enter the IP address of a DNS server. If you enter a domain name instead of an IP address in server-related fields, e.g., FTP, SMTP or NTP server, then the camera will need a DNS server to translate domain names into an IP address that is actually used for communication on the Internet.
- **HTTP Port:** Use the standard HTTP port number 80 or alternatively specify another port number between 1025 and 65535.

If you choose to use a non-standard port, and the camera on the LAN is to be accessible from the Internet, then you must configure your router/firewall to forward incoming HTTP request to that specified port (via NAT/port forwarding settings).

- **MAC:** Display the MAC address of the camera. Each camera comes with a unique MAC address, which is indicated on the product label. It helps you to identify which camera is currently accessed, particularly when multiple cameras are connected to your network.

4.3.2 FTP

To allow the camera to upload recorded video clips/JPEG files to an FTP server, you have to specify an FTP server and configure related settings.

FTP	
Basic Setting	
FTP Server IP:	<input type="text" value="192.168.1.1"/>
FTP Server Port:	<input type="text" value="21"/> [20,21,1024~ 65535]
User Name:	<input type="text"/>
Password:	<input type="password"/>
File Upload Path:	<input type="text" value="default_folder"/>
<input type="button" value="Save"/>	

- **FTP Server IP:** Enter the IP address of the FTP server.
- **FTP Server Port:** Enter the port number of the FTP server.
- **User Name:** Enter the user name to logon to the FTP server.

- **Password:** Enter the password to logon to the FTP server.
- **File Upload Path:** Specify the folder which has been created under FTP server root directory.

4.3.3 SMTP

To enable the camera to send you email notifications when an alarm is triggered, you need to specify an SMTP server to send the emails.

SMTP
Basic Setting
☐ My Server Requires Authorization.
SMTP Server IP:
User Name:
Password:
Sender:
Receiver:

- **My Server Requires Authorization:** If your SMTP server requires authorization to send emails, enable this option.
- **SMTP Server IP:** Enter the IP address of the SMTP server.
- **User Name:** Enter the user name to log on to the SMTP server.
- **Password:** Enter the password to log on to the SMTP server.
- **Sender:** Enter the email address to be shown as the sender of the notification email.
- **Receiver:** Enter the email address to which the notification email is sent.

4.3.4 NTP

If you want the camera to synchronize its time clock with an NTP (Network Time Protocol) sever, configure the NTP server settings here.

NTP

Basic Setting

NTP Server:

Time Zone:

GMT+08 Taipei, Beijing, Hong Kong ▼

☐ Automatically Adjust for Daylight Saving Time Changes.

Save

- **NTP Server:** Enter the IP address or the domain name of the NTP server to synchronize with.
- **Time Zone:** Select a time zone in which the camera is located.
- **Automatically Adjust for Daylight Saving Time Changes:** Check to apply the daylight saving time automatically.

4.3.5 RTSP

RTSP is a standard for connecting a client to establish and control streaming data over the web. If you want to allow third-party devices or software to access video/audio streams from the IP camera over the network, you must configure the RTSP ports. You can provide up to 6 streams according to the specific codec mode with different RTSP port.

RTSP

RTSP Port Setting

Stream 1:	<input type="text" value="8555"/>	MJPEG/Primary
Stream 2:	<input type="text" value="554"/>	MPEG4/Primary
Stream 3:	<input type="text" value="8554"/>	MPEG4/Secondary
Stream 4:	<input type="text" value="8558"/>	MJPEG/Third
Stream 5:	<input type="text" value="8556"/>	H.264/Secondary
Stream 6:	<input type="text" value="8557"/>	H.264/Primary

Port Value Range:(554~65535)

Save

To use an RTSP player to access the camera's streams, you have to use correct the RTSP URL to request the streams. Refer to the table below for RTSP URLs:

Stream	URL
MJPEG Primary	rtsp://192.168.1.30:8555/mjpeg
MJPEG Third	rtsp://192.168.1.30:8558/mjpeg
H.264 Primary	rtsp://192.168.1.30:8557/h264
H.264 Secondary	rtsp://192.168.1.30:8556/h264
MPEG4 Primary	rtsp://192.168.1.30:554/mpeg4
MPEG4 Secondary	rtsp://192.168.1.30:8554/mpeg4

*Replace the IP address and the port number with the camera's settings if otherwise configured.

4.3.6 ONVIF

ONVIF is a standard that ensures interoperability between IP-based physical security products regardless of the manufacturers. This camera is ONVIF compliant and you can configure whether the camera can be found by other ONVIF compliant products and the related settings.

ONVIF

Basic Settings

☒ Discovery via ONVIF.

☒ Accept command/functionality outside of Discovery capability.

☐ User Authentication.

Save

Basic Settings

- **Discovery via ONVIF:** Check the box if you want the camera to be found by other ONVIF compliant devices in a network, e.g., an ONVIF compliant NVR.
- **Accept command/functionality outside of Discovery capability:** If checked, the camera is allowed to accept commands from ONVIF compliant device thus changing the camera's functionality.
- **User Authentication:** If an ONVIF compliant device needs authentication for communication, enable this option.

4.4 System

4.4.1 Date and Time

Date & Time

Current Time

Date: 2011-3-10
Time: 08:57:49

New Time

☐ Set Manually

Date: 2011-3-23
Time: 21:4:9

☐ Synchronize with Computer Timer

Date: 2011-3-23
Time: 21:05:28

☐ Synchronize with NTP Server

NTP Server: tw.pool.ntp.org
Time Zone: GMT+08 Taipei, Beijing, Hong Kong

Date Format: YYYY/MM/DD

Save

Current Time

Displays the current date and time of the camera. Date and time will be updated after you configure new settings in the **New Time** section and click **Save** to apply the settings.

New Time

You can set the camera time by one of the following methods:

- **Set Manually:** Manually enter the camera's date and time settings in the given fields.
- **Synchronize with Computer Timer:** Use this option to synchronize the camera's date and time with the computer timer.
- **Synchronize with NTP Server:** Use this option to synchronize the camera's date and time with an NTP (Network Time Protocol) server, which can be configured under **Network > NTP**.
- **Date Format:** Allows you to specify a desired date format.

4.4.2 Time Stamp

The **Time Stamp** function allows you to overlay the date and time stamp on the video. When enabled, the recorded video will be displayed with the date and the time.

Time Stamp

☐ Enable Date and Time Stamp

Date Format: YYYY/MM/DD

Save

- **Enable Date and Time Stamp:** Check this box to enable the date and time stamp on images/video clips; to disable this function, uncheck the box.
- **Date Format:** Select the desired date format for the time stamp.

4.4.3 Firmware

Firmware

Current Version Description

Kernel Version: Linux version 2.6.18_v1.5.1 _2M_MS03

App Version: AP_01-00-58_2M_MS03

Specify the Firmware to Update:

Browse...

Update

Note: Do not disconnect the power of the device, during the update.

!!Restart Camera will cause disconnect.

Restart Camera

!!Reset all of the camera parameters to default except Network..

Factory Default

!!Reset all of the camera parameters to default.

Hard Factory Default


Current Version Description: Displays the current version of the firmware.

Specify the Firmware to Update: This function is designed to update the firmware of the camera. To perform the firmware upgrade, follow these parameters:

- Keep the network connected during the update process.
- DO NOT turn off or restart the camera during the firmware update process.

To update the firmware:

1. Click the **Browse** button to locate the firmware file.
2. Click the **Update** button to start update.
3. When prompted, click **OK** to proceed.



4. Wait about 20~60 seconds until the file is successfully updated. Once the update is completed, the browser will show a message reads "Firmware update successful". Then it will take 60 seconds to restart the camera.

Firmware update successful.
Camera is rebooting, please wait...

5. The utility will automatically go back to live view screen after firmware has been updated successfully.

You can also perform these tasks on the **Firmware** page:

- **Restart camera:** Restart the camera. This will cause all streams to disconnect.
- **Factory Default:** Reset all of the camera settings to the defaults, except network settings. After you confirm to reset, the camera will reset and restart automatically. When complete, you will return to the live view page.
- **Hardware Factory Default:** Reset all of the camera parameters to the defaults, including the network settings.

4.4.4 User Management

The **User Management** page allows you to manage user accounts and access privileges.

User Management

User List

admin: [Admin]

Delete User

Add/Modify User

User Name:

Password:

Confirm:

Authority: ☐ Admin ☒ Viewer

User Add

User List

Displays the list of current user accounts of the camera. To delete a user account, select the unwanted user account from the list and then click **Delete User**.


Add/Modify User

You can add a new user or modify current user's account or authority.

- To add a new user, enter the user name and password and specify the authority. Then click **User Add** to add a user.
- To modify the password of the existing user, enter the user name and modify the password.
- Two types of account can be specified:
 - **Admin (Administrator):** Can access all camera functions, pages and make configurations.
 - **Viewer (Guest):** Can only access the live view page and take snapshots.

4.4.5 Language

The **Language** drop-menu allows you to change the language of the web interface. Supported languages include English, Spanish, Italian, Simplified Chinese and Traditional Chinese. Click **Save** to apply the language setting, and the browser will automatically refresh to reflect the change.



Language


Basic Setting

Language English

Save

4.4.6 Log

This page displays detailed information about the camera's operations and activities, including all the login and alarm records.



Log

#011.2011-03-23	21:56:33	Blur alarm
#012.2011-03-23	21:55:35	Blur alarm
#013.2011-03-23	21:54:36	Blur alarm
#014.2011-03-23	21:53:37	Blur alarm
#015.2011-03-23	21:52:38	Blur alarm
#016.2011-03-23	21:51:39	Blur alarm
#017.2011-03-23	21:50:40	Blur alarm
#018.2011-03-23	21:49:41	Blur alarm
#019.2011-03-23	21:48:42	Blur alarm
#020.2011-03-23	21:47:43	Blur alarm
#021.2011-03-23	21:46:03	Blur alarm
#022.2011-03-23	21:45:04	Blur alarm
#023.2011-03-23	21:44:05	Blur alarm
#024.2011-03-23	21:43:06	Blur alarm
#025.2011-03-23	21:42:07	Blur alarm
#026.2011-03-10	06:48:35	admin login on 192.168.1.33
#027.2011-03-10	04:47:30	admin login on 192.168.1.14

4.4.7 Audio

Audio

Audio Receiving

☒ OFF
 ☐ ON

Audio Playing

☒ OFF
 ☐ ON

Audio Volume

(1~4)

Save

Note:

1.Audio receiving means a PC or other devices may receive the audio transmitted from Camera through audio input jack.

2.Audio playing means Camera may play the audio or soundtrack transmitted from a PC or other devices through the audio output jack.

3.Camera may play the default siren sound once an alarm is triggered.

4.Each audio function is only activated in Live view mode.

- **Audio Receiving:** If a microphone is connected to the camera, you can select **ON** to allow the camera to record the audio and transmit to your PC. This enables the camera to pick up sounds in the background.
- **Audio Playing:** If a speaker is connected to the camera, you can select **ON** to allow the camera to play the audio transmitted from your PC. This enables you to speak to the person(s) around the camera.
- **Audio Volume:** Allows you to adjust both the audio playing and recording volume of the camera.

Using the two-way audio function

Note that the two-way audio function is **only active in the live view page** using the web browser. To use the two-way audio function:

1. Make sure a speaker is connected to the **Audio Out** port and a microphone is connected to the **Audio In** port of the camera.
2. Enter **System > Audio** and enable both the **Audio Receiving** and **Audio Playing** functions. Then adjust the audio volume to the desired level.
3. To access the two-way audio streams:
4. Make sure your computer is connected to a microphone and speaker. Enter the **live view page** of the web-based utility.
5. Speak into the microphone and the person(s) around the camera should hear your voice.
6. When people around the camera are talking to you, you should hear them from the speaker that is connected to the computer.

4.5 Event

When an event occurs, it triggers an alarm and the camera will take a pre-defined action, e.g., sending a recorded video clip or JPEG files to a designated server. With this camera, an event can be triggered by external alarm devices or the camera's detection mechanism, including motion, blur, audio and Ethernet detection.



Note

1. When there is more than one recording to be carried out at the same time, the scheduled video recording takes top priority, followed by the recording triggered by an Ethernet disconnection and lastly the recording triggered by other events.
2. Only one event will be handled at a time. If an event is already triggered, other event will be logged to the system but no action will be taken.

4.5.1 Motion Detection

When the **Motion Detection** is enabled, the camera detects motion under a pre-specified condition within a designated area. When motion is detected, the camera will generate an alarm and then take a specified action.

Note that to use the motion detection function, the following two conditions must be met:

1. You must select MJPEG codec for one of the streams to enable the live view.
2. You must select H.264 or MPEG4 codec for one of the streams to process the motion detection.

Motion Detection

Configuration


Motion Sensitivity:

Highest

50
(Customized Threshold [1~100])

Save

Motion Area Setting



Save Motion Area

Action

☒ OFF
☐ FTP
☐ SMTP
☐ SD Card

Save

Configuration

- **Motion Sensitivity:** Specify the sensitivity to moving objects before the camera triggers an alarm. The higher the sensitivity, the slighter the movement is required to set off an alarm. You can alternatively select **User Define** and enter a value from 1 to 100 in the **Customized Threshold** field. When the motion within a specified area exceeds the threshold, an alarm will be triggered.

Select **OFF** to disable the motion detection

Motion Area Setting

- **Motion area setting:** Click target squares displayed on the screen to define detection areas; once configured, click **Save Motion Area** to save settings.

Action

Specify the action to be taken when an alarm is triggered upon motion detection:

- **OFF:** No action will be taken, but an alarm will be logged.
- **FTP:** Recorded video clips/JPEG files will be uploaded to the FTP server when alarm is triggered.
- **SMTP:** Notification email with the recorded JPEG files attached will be sent to the SMTP server.
- **SD Card:** Recorded video clips will be saved to the SD card when the alarm is triggered.

4.5.2 External Alarms

If external alarm devices, e.g., sensors and alarms, are connected to the camera's alarm input/output, the following settings must be made:

External Alarms			
Configuration			
	Setting	Level	
Alarm In1	<input checked="" type="radio"/> Disable <input type="radio"/> Enable	<input checked="" type="radio"/> Low	<input type="radio"/> High
Alarm In2	<input checked="" type="radio"/> Disable <input type="radio"/> Enable	<input checked="" type="radio"/> Low	<input type="radio"/> High
Alarm Out	<input checked="" type="radio"/> Disable <input type="radio"/> Enable	<input checked="" type="radio"/> Low	<input type="radio"/> High
Action			
Alarm In1	<input checked="" type="radio"/> OFF <input type="radio"/> FTP <input type="radio"/> SMTP <input type="radio"/> SD Card		
Alarm In2	<input checked="" type="radio"/> OFF <input type="radio"/> FTP <input type="radio"/> SMTP <input type="radio"/> SD Card		
<input type="button" value="Save"/>			

Configuration

- **Setting:** Enable the Alarm I/O that is connected with the respective external alarm device.

- **Level:** Set the (electricity) current as low or high to define the active state.

Action

Specify the action to be taken when external alarm is triggered:

- **OFF:** No action will be taken, but an alarm will be logged.
- **FTP:** Recorded video clips/JPEG files will be uploaded to the FTP server when alarm is triggered.
- **SMTP:** Notification email with the recorded JPEG files attached will be sent to the SMTP server.
- **SD Card:** Recorded video clips will be saved to the SD card when the alarm is triggered.



Note

To perform a video recording, you must select MJPEG codec for one of the streams.

4.5.3 Blur Detection

With the **Blur Detection** enabled, when the camera detects incidents that make video image blur, e.g. redirection, blocking or defocusing, the camera will generate an alarm and then take a specified action.



Note

Note that to use the blur detection function, the following two conditions must be met:

1. You must select MJPEG codec for one of the streams to enable the live view.
2. You must select H.264 or MPEG4 codec for one of the streams to process the motion detection.

Blur Detection	
Configuration	
Blur Detection:	<input checked="" type="radio"/> Disable <input type="radio"/> Enable
Sensitivity:	<input type="text" value="50"/> seconds (10~600)
<input type="button" value="Save"/>	
Action	
<input checked="" type="radio"/> OFF <input type="radio"/> FTP <input type="radio"/> SMTP <input type="radio"/> SD Card	
<input type="button" value="Save"/>	

Configuration

- **Blur Detection:** Select **Enable** to enable Blur Detection; select **Disable** to disable this function.
- **Sensitivity:** You can alternatively customize the camera's sensitivity to a blur. The camera will judge whether it has been tampered based on the sensitivity threshold specified.

Action

- **OFF:** No action will be taken, but an alarm will be logged.
- **FTP:** Recorded video clips/JPEG files will be uploaded to the FTP server when alarm is triggered.
- **SMTP:** Notification email with the recorded JPEG files attached will be sent to the SMTP server.
- **SD Card:** Recorded video clips will be saved to the SD card when the alarm is triggered.

4.5.4 Audio Detection

With the **Audio Detection** enabled, when the camera detects any sound, the camera will generate an alarm and then take a specified action.

Configuration

- **Audio Sensitivity:** Specify the camera's sensitivity level to the audio signal. The higher the sensitivity, the lower the volume is required to set off an alarm.

When set to **OFF**, the audio detection is disabled.

Action

Specify the action to be taken when an alarm is triggered upon audio detection:

- **OFF:** No action will be taken, but an alarm will be logged.
- **FTP:** Recorded video clip will be uploaded to the FTP server when the alarm is triggered.
- **SMTP:** A notification email attached with the recorded video clip will be sent to the SMTP server.
- **SD Card:** Recorded video clip will be saved to the SD card when the alarm is triggered.



Note

To perform a video recording, you must select MJPEG codec for one of the streams.

4.5.5 Ethernet Detection

With **Ethernet detection** enabled, when the camera detects an Ethernet disconnection, the camera will generate an alarm and then take a specified action.

Ethernet Detection

Configuration

Setting

Trigger an Alarm when Ethernet is Disconnected. ☒ Disable ☐ Enable

Action

☒ OFF ☐ SD Card

Save

Configuration

- **Trigger an Alarm When Ethernet is Disconnected:** Select whether to disable/enable this function.

Action

Specify the action to be taken when an alarm is triggered upon audio detection:

- **OFF:** No action will be taken, but an alarm will be logged.
- **SD Card:** Recorded video clips will be saved to the SD card in AVI format when the alarm is triggered.



Note

Regardless of your settings in **Recording > SD card**, when an Ethernet disconnection is triggered, the video clip recording will always be saved in AVI format.

4.5.6 Event Management

Event Management

Basic Setting

Alarm Duration 10 Second(s) ▼

Alarm Reset Reset

Save

Basic Setting

- **Alarm Duration:** Specify the duration of the alarm when an event is triggered.
- **Alarm Reset:** Use this button to stop the current alarm and to restart event detection again.

4.6 Recording

Recording allows you to configure recording-related settings and schedule recording. The defaults are listed in the table below:

4.6.1 Settings – Video Clip

Configure the duration and format of video to be recorded when an alarm is triggered.

Video File

Basic

AVI Duration:

-- ▾

Second(s)

AVI Format:

MPEG4(D1) ▾

Save

1.If you also insert the SD card in IPNetcam, then AVI Duration option cannot be selected.

2.AVI duration can only be set before SD card is insert.

Basic Settings

- **AVI Duration:** Select video duration.
- **AVI Format:** Select a desired video format. Available formats depend on the primary and the secondary streaming codec/resolution settings.

4.6.2 Settings – FTP

FTP	
FTP Networking	
FTP Server IP:	192.168.1.1
User Name:	
File Upload Path:	default_folder
Storage Setting	
Upload File Numbers	<input type="text" value="1"/> (1~20)
File Format:	AVI <input type="button" value="v"/>
<input type="button" value="Save"/>	

FTP Networking

Displays the current FTP settings, which are specified via **Network > FTP**.

Storage Setting

- **Upload File Numbers:** Enter the number of JPEG files to be uploaded to the FTP per event.
- **File Format:** Select the format in which to upload the recorded video file to the FTP server when an event has been triggered.
 - **JPEG files:** The camera will record specified number of JPEG files and upload to the FTP server.
 - **AVI files:** The camera will record AVI files and upload to the FTP sever. For the duration and AVI format, see **Recording > Setting > Video File**.

4.6.3 Settings – SMTP

SMTP

SMTP Networking

SMTP Server IP: 192.168.1.1

Email Address:

Storage Setting:

Attached File Numbers: (1~20)

Attached File Format: JPEG

Save

1. The file number could be limited since the client's SMTP server may regulate & restrain the data volume from senders.

SMTP Networking

Displays the current SMTP settings, which are specified via **Network > SMTP**.

Storage Setting

- **Attached File Numbers:** Enter the number of JPEG images that will be attached to the notification email. Set a lower number if SMTP server has an email size limit.

4.6.4 SD Card Storage Format Selection

SD Card Storage Format Selection

Storage Setting

File Format:	AVI
Capability:	0(MB)
Usage:	100%

SD Card Format

SD Card Unmount

SD Card Overwrite: ☒ OFF ☐ ON

Save

If you want SD card to recycle the capacity, please set up the overwrite function before the SD card starts recording. The overwrite function will not be activated during recording to SD card.

Storage Setting

- **File Format:** Specify the format of the video to be saved to the SD card when an event is triggered.
- **Capacity/Usage:** Shows the card capacity and the space usage percentage.
- **SD Card Format:** Use this button to format the SD card. This option is not available if an SD card has not been inserted in the camera.
- **SD Card Unmount:** Click this button before safely removing the SD card. This option is not available if an SD card has not been inserted in the camera.
- **SD Card Overwrite:** Select **ON** to enable overwriting once the storage is full.

4.6.5 Period Setting

The Period Setting allows you to schedule video recordings at specified times. Set the automatic recording times by selecting the desired weekday and the period of time. Up to 7 scheduled recordings can be set. Check **Save to SD Card** should you wish to save the recorded video clips to the SD card.

Period Setting

Basic Setting

<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼
<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼
<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼
<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼
<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼
<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼
<input type="checkbox"/>	Monday	▼	From	0	▼	:	0	▼	To	0	▼	:	0	▼

☐ Save to SD card.

Save

The "AVI duration"(in Recording->Setting->Video File)and "Alarm duration"(in Event->Event Management) will not work once any schedule period is set.



Note

The scheduled recording always demands higher priority than the alarm-based recording. When a scheduled recording is proceeding, the alarm-based recording will be disabled but the alarms will be logged.