

POE-SW1616 16 Port POE Switch



The POE-SW1616 unmanaged POE switch with 16 10/100Mbps RJ45 ports, 2 Gigabit copper / SFP combo uplink port reduces the amount of equipment and installation costs by delivering data and power over a single Ethernet cable. It features a switching capacity of 7.2Gbps. LED indicators display the device status for easy power management and troubleshooting. An internal power supply reduces clutter and delivers up to 30 watts per port.

Fast Ethernet Ports	16 10/100 Base-TX Tj45 Auto MDI / MDI-X Ports
Gigabit Ports	2 Gigabit SFP +2 Gigabit Uplink
Power over Ethernet Ports	16 Port with POE Injector Function
Max Power Distance	Up to 100 Meters / 300 Feet
Switch Fabric	7.2Gbps
Flow Control	Back Pressure for half duplex, IEEE 802.3x Pause Frames for full duplex
Power Requirement	100 ~ 240V AC, 50 ~ 60Hz
Temperature	Operating: 0 ~ 40°C / Storage: -40 ~ 70°C
Humidity Operating	5% to 90%, Storage: 5% ~ 90% (Non-condensing)
Warranty	2 Years
Power over Ethernet	
POE Standard	IEEE 802.3AF/AT Power over Ethernet / PSE
POE Power Supply Type	End-Span
POE Power Output	Per Port 48V DC, Max 30 Watts
Power Pin Assignment	1/2(+), 3/6(-)
Power Dissipation	250 Watts
Standard Conformance	FCC, CE, ROHS
Dimensions	440mm x 270mm x 44mm
Mounts	Rack Mountable with Standard Rack
Switch Processing Scheme	Store and Forward

For more information about the POE-SW1616, please [click here](#).