



CC8370-HV

Fisheye Network Camera

3MP · WDR Pro · 3DNR · 180° Panoramic View · IK10 · IP66 · SNV


VIVOTEK's CC8370-HV is a Vandal-proof cube network camera offering up to 30 fps @ 3-Megapixel resolution. Its unique design makes it the best choice for boutique, department or convenience stores.

The CC8370-HV can view at a wide angle of 180 degrees, providing complete video security with no dead angles. Featuring with WDR Pro, the camera captures both the dark and bright areas of an image and combines the differences to create a highly realistic representation of the original scene, and with SNV technology, it makes high-quality full-color surveillance video possible under low-light conditions. These features enable the camera to provide video quality nearing the capabilities of the human eye. The unique mounting design facilitates easy installation on a wall or desktop in order to capture faces at eye level. A built-in microphone which records sound within a 5 meter radius further increases the level of surveillance.

The CC8370-HV also supports the industry-standard H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. Together with the ST7501 multi-lingual 32-channel recording software, users can simply and quickly set up an easy-to-use IP surveillance system.

Key Features

- 3-Megapixel CMOS Sensor
- 30fps @ 2048x1536
- WDR Pro (100dB) to Provide Extreme Visibility in High Light Contrast Scenes
- SNV (Supreme Night Visibility)
- 3D Noise Reduction for Low-light Conditions
- Video Rotation
- 180° Horizontal Panoramic View
- Real-time H.264 and MJPEG Compression (Dual Codec)
- Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
- Built-in IEEE 802.3af Compliant PoE
- Built-in Microphone
- Built-in MicroSD/SDHC/SDXC card slot
- ±25° Tilt Lens
- Anti-Hanging Design



The World's First Adjustable FOV Fisheye Camera



Jail



Retail Store



180° Panoramic View

Technical Specifications

| | | | |
|--------------------------------------|---|-------------------------------|--|
| Model | CC8370-HV | Interface | 10Base-T/100 BaseTX Ethernet (RJ-45) |
| System Information | | ONVIF | Supported, specification available at www.onvif.org |
| CPU | Multimedia SoC (System-on-Chip) | Intelligent Video | |
| Flash | 128 MB | Video Motion Detection | Five-window video motion detection |
| RAM | 256 MB | Alarm and Event | |
| Camera Features | | Alarm Triggers | Video motion detection, manual trigger, periodical trigger, system boot, recording notification, camera tampering detection, audio detection |
| Image Sensor | 1/3 Progressive CMOS | Alarm Events | Event notification using HTTP, SMTP, FTP, NAS server and SD Card File upload via HTTP, SMTP, FTP, NAS server and SD card |
| Maximum Resolution | 2048x1536 | General | |
| Lens Type | Fixed-focal | Connectors | RJ-45 for Network/PoE connection |
| Focal Length | 1.6 mm | LED Indicator | System power and status indicator |
| Aperture | F2.0 | Power Input | IEEE 802.3af PoE Class 1 |
| Field of View | 180° (horizontal) 130° (vertical) 180° (diagonal) | Power Consumption | PoE Max. 4.9 W |
| Shutter Time | 1/5 sec. to 1/32,000 sec. | Dimensions | 115 (D) x 65 (W) x 59 (H) mm |
| WDR Technology | WDR Pro | Weight | Net: 331g |
| Minimum Illumination | 0.05 Lux @ F2.0 (Color) | Casing | IP66, IK10 |
| Pan/tilt/zoom Functionalities | ePTZ: 4x digital zoom IE plug-in | Safety Certifications | CE, LVD, FCC Class B, VCCI, C-Tick, UL |
| On-board Storage | MicroSD/SDHC/SDXC card slot | Operating Temperature | Starting Temperature: 0°C ~ 50°C (32°F~ 122°F) Working Temperature: -10°C ~ 50°C (14°F~ 122°F) |
| Video | | Warranty | 24 months |
| Compression | H.264 & MJPEG | System Requirements | |
| Maximum Frame Rate | 30fps @ 2048x1536 | Operating System | Microsoft Windows 8/7/Vista/XP/2000 |
| Maximum Streams | 3 simultaneous streams | Web Browser | Mozilla Firefox 7~10 (streaming only) Internet Explorer 7/8/9/10 |
| S/N Ratio | 58.8 dB | Other Players | VLC: 1.1.11 or above Quicktime: 7 or above |
| Dynamic Range | 100 dB | Included Accessories | |
| Video Streaming | Adjustable resolution, quality and bitrate | Others | Quick installation guide, warranty card, mounting bracket, screw pack |
| Image Settings | Adjustable image size, quality and bit rate; Time stamp, text overlay, flip & mirror & rotate; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings | Dimensions | |
| Audio | | | |
| Audio Capability | Audio input | | |
| Compression | G.711, G.726 | | |
| Interface | Built-in Microphone | | |
| Effective Range | 5 meters | | |
| Network | | | |
| Users | Live viewing for up to 10 clients | | |
| Protocols | IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP | | |

All specifications are subject to change without notice. Copyright © VIVOTEK INC. All rights reserved.

