



Fixed Dome Network Camera FD8137HV



1MP • WDR Pro • 15M IR • IP66 •
Vandal-proof • 3DNR

VIVOTEK FD8137HV is an easy-to-use fixed dome network camera specifically designed for indoor/outdoor security applications with a compact, stylish vandal-proof exterior. It features an HD WDR CMOS sensor to cope with challenging lighting conditions. The WDR Pro Technology allows the camera to capture both dark and bright parts of an image and combines the differences to generate a highly realistic image representative of the original scene, enabling it to provide video quality close to the capabilities of the human eye. This function enables the FD8137HV to be widely applicable in high contrast environments such as lobby entrances, parking lots, ATMs, loading areas, and much more.




In order to adapt to constantly changing outdoor lighting conditions, the FD8137HV features a removable IR-cut filter as well as improved IR illuminators effective up to 15M for superior image quality around the clock. For protection against harsh outdoor environments, the camera is encased in an IP66-rated housing to withstand rain and dust. Furthermore, the metal vandal-proof housing effectively provides robust protection from vandalism.

The FD8137HV supports the industry-standard H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. With H.264, and MJPEG compatibility both included, the dual streams can be simultaneously transmitted in any of these formats at different resolutions, frame rates, and image qualities for versatile platforms. Thereby it further optimizes bandwidth and storage efficiency.

Incorporating a number of advanced features standard for VIVOTEK cameras, including tamper detection, 802.3af compliant PoE, MicroSD/SDHC/SDXC card slot, and VIVOTEK's 32-channel recording software, the FD8137HV is the ideal solution for your indoor/outdoor surveillance needs.

Features

- 1-Megapixel CMOS Sensor
- 30 fps @ 1280x800
- Real-time H.264, MJPEG Compression (Dual Codec)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 15 Meters
- WDR Pro for Unparalleled Visibility in High Contrast Environments
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- Weather-proof IP66-rated Housing
- 3D Noise Reduction for Low-light Conditions



Technical Specifications

Models	FD8137HV-F3 FD8137HV-F6	Network	
System Information		Users	Live viewing for up to 10 clients
CPU	Multimedia SoC (System-on-Chip)	Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X
Flash	128MB	Interface	10Base-T/100 BaseTX Ethernet (RJ-45)
RAM	256MB	ONVIF	Supported, specification available at www.onvif.org
Camera Features		Intelligent Video	
Image Sensor	1/3" Progressive CMOS	Video Motion Detection	Triple-window video motion detection
Maximum Resolution	1280x800 (1MP)	Alarm and Event	
Lens Type	Fixed-focal	Alarm Triggers	Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection
Focal Length	f = 3.6 mm (FD8137HV-F3) f = 6 mm (FD8137HV-F6)	Alarm Events	Event notification using digital output, HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server
Aperture	F1.8 (FD8137HV-F3) F1.6 (FD8137HV-F6)	General	
Field of View	FD8137HV-F3: 86° (Horizontal) 51° (Vertical) 103° (Diagonal) FD8137HV-F6: 59° (Horizontal) 32° (Vertical) 70° (Diagonal)	Connectors	RJ-45 for Network/PoE connection Digital input*1
Shutter Time	1/5 sec. to 1/32,000 sec.	LED Indicator	System power and status indicator
WDR Technology	WDR Pro	Power Input	IEEE 802.3af PoE Class 2
Day/Night	Removable IR-cut filter for day & night function	Power Consumption	Max. 5.1W
Minimum Illumination	FD8137HV-F3: 1.05 Lux @ F1.8, 50 IRE (Color) 0.001 Lux @ F1.8, 50 IRE (B/W) FD8137HV-F6: 0.48 Lux @ F1.6, 50 IRE (Color) 0.001 Lux @ F1.6, 50 IRE (B/W)	Dimensions	Ø: 152 mm x 94 mm
Pan Range	350°	Weight	Net: 666 g
Tilt Range	60°	Casing	Weather-proof IP66-rated housing Vandal-proof IK10-rated housing
Rotation Range	350°	Safety Certifications	CE, LVD, FCC Class A, VCCI, C-Tick
Pan/tilt/zoom	ePTZ:	Operating Temperature	Starting Temperature: -10°C ~ 50°C (14°F~ 122°F) Working Temperature: -20°C ~ 50°C (-4°F~ 122°F)
Functionalities	48x digital zoom (4x on IE plug-in, 12x built-in)	Warranty	24 months
IR Illuminators	Built-in IR illuminators, effective up to 15 meters IR LED*8	System Requirements	
On-board Storage	MicroSD/SDHC/SDXC card slot	Operating System	Microsoft Windows 7/Vista/XP/2000
Video		Web Browser	Mozilla Firefox 7~10 (streaming only) Internet Explorer 7/8/9
Compression	H.264 & MJPEG	Other Players	VLC: 1.1.11 or above QuickTime: 7 or above
Maximum Frame Rate	30 fps @ 1280x800 In both compression modes	Included Accessories	
Maximum Streams	2 simultaneous streams	CD	User's manual, quick installation guide, Installation Wizard 2, ST7501 32-channel recording software
S/N Ratio	Above 53 dB	Others	Quick installation guide, warranty card, alignment sticker, screw pack, software CD
Dynamic Range	110 dB	Dimensions	
Video Streaming	Adjustable resolution, quality and bitrate Configurable video cropping for bandwidth saving		
Image Settings	Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings, 3D Noise Reduction		
Audio			
Audio Capability	Audio input		
Compression	G.711 / G.726		
Interface	Built-in microphone		
Effective Range	5 meters		

Compatible Accessories

Mounting Kits




AM-211
L-shape wall mount

PoE Kits



POE-IJ-1748NDN
802.3af Compliant PoE Injector



All specifications are subject to change without notice. Copyright © 2013 VIVOTEK INC. All rights reserved.

Distributed by:



VIVOTEK INC.

6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C.
| T: +886-2-82455282 | F: +886-2-82455532 | E: sales@vivotek.com

