



Speed Dome Network Camera SD8364E



1080p HD • 30x Zoom • NEMA 4X • IP66 •
Defog • -40 °C ~ 55 °C • EIS • PoE Plus


VIVOTEK SD8364E is part of the SUPREME series product line offering 1080p Full HD resolution with superb image quality. Adopting a 30x optical zoom lens, the SD8364E is able to capture details at top-notch quality. The IP66- and NEMA 4X-rated housing protects the camera body against rain, dust and corrosion within a wide temperature range between -40 °C to 55 °C. This feature ensures operation under extreme weather conditions and hazardous environments. It is especially suitable for monitoring wide open indoor/outdoor spaces such as airports, highways and parking lots where high-level reliability and precision are always required.

The SD8364E supports high-performance H.264/MPEG-4/MJPEG compression technology and offers extra smooth video quality with resolution up to 30 fps @ 1080p. Boasting WDR Pro technology, the SD8364E can also cope with challenging lighting conditions and generate image quality close to the capabilities of the human eye. With a sophisticated pan/tilt mechanism, the camera provides fast, precise movement with continuous 360-degree pan and 220-degree tilt. Users can also easily control the lens position via a mouse or a joystick to track the object of interest and set up to 128 preset positions for patrolling. With the built-in auto tracking feature, the SD8364E provides instantaneous reaction to suspicious moving objects in wide area locations before operators are aware of activity.

As with all VIVOTEK true day/night cameras, the SD8364E features a removable IR-cut filter, maintaining clear images 24 hours a day. With audio detection, by recognizing increases or decreases in sound volume, an additional layer of intrusion detection is ensured. With other advanced features such as SD/SDHC/SDXC card slot, 802.3at compliant PoE Plus and 60 fps high quality video, the SD8364E is the best choice for the most demanding outdoor surveillance applications.

Features


- 1080p Full HD SONY CMOS Sensor
- 30 fps @ 1080p Full HD; 60 fps @ 720p HD
- 30x Zoom Lens
- Removable IR-cut Filter for Day & Night Function
- 360° Continuous Pan and 220° Tilt
- Real-time H.264, MPEG-4 and MJPEG Compression (Triple Codec)
- WDR Pro for Unparalleled Visibility in High Contrast Environments
- Weather-proof IP66-rated and NEMA4X Housing
- -40 °C ~ 55 °C Wide Temperature Range for Extreme Weather Conditions
- Audio Detection for Instant Alerts
- Auto Tracking for Moving Objects
- Built-in 802.3at Compliant PoE Plus
- 3D Privacy Masks for Additional Protection
- Built-in SD/SDHC/SDXC Card Slot for On-board Storage
- Defog



Technical Specifications

Model	SD8364E SD8364E-M (With Electric Dehumidifier)	Intelligent Video	
System Information		Video Motion Detection	Triple-window video motion detection
CPU	Multimedia SoC (System-on-Chip)	Auto-Tracking	Auto-tracking on moving object
Flash	128 MB	Alarm and Event	
RAM	256 MB	Alarm Triggers	Video motion detection, manual trigger, periodical trigger, system boot, recording notification, camera tampering detection, audio detection
Camera Features		Alarm Events	Event notification using digital output, HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server
Image Sensor	1/2.8" Progressive CMOS	General	
Maximum Resolution	1920x1080	Connectors	RJ-45 cable connector for Network/PoE connection Audio input Audio output AC 24V power input Digital input*4 Digital output*2 RS-485 for PTZ control (PelcoD protocol, Baud rate 2400)
Lens Type	30x Optical Zoom, Auto Focus	LED Indicator	System power and status indicator
Focal Length	f = 4.3~129 mm (30x zoom)	Power Input	PoE plus (IEEE 802.3at compliant) High Power PoE AC 24V
Aperture	F1.6 ~ F4.7	Power Consumption	PoE plus: Max. 19W AC 24V: Max. 48W (heater on) Max. 19W (heater off) High Power PoE: Max. 48W (heater on) Max. 19W (heater off)
Auto-iris	DC-iris	Dimensions	Ø: 205 mm x 321 mm
Field of View	2.3° ~ 64° (horizontal) 1.3° ~ 36° (vertical) 2.6° ~ 73° (diagonal)	Weight	Net: 3,660 g
Shutter Time	1/1 sec. to 1/10,000 sec.	Casing	Weather-proof IP66- and NEMA 4X-rated metal housing Built-in electrical dehumidifier device (SD8364E-M)
WDR Technology	WDR Pro	Safety Certifications	CE, FCC Class A, VCCI, C-tick, NEMA 4X
Day/Night	Removable IR-cut filter for day & night function	Operating Temperature	-5°C ~ 55°C (PoE Plus) -40°C ~ 55°C (AC 24V) -40°C ~ 55°C (High Power PoE)
Minimum Illumination	0.5 Lux @ F1.6, 30 IRE (Color) 0.03 Lux @ F1.6, 30 IRE (B/W)	Warranty	36 months
Pan Speed	0.05° ~ 450° / sec	System Requirements	
Pan Range	360 endless	Operating System	Microsoft Windows 7/Vista/XP/2000
Tilt Speed	0.05° ~ 450° / sec	Web Browser	Mozilla Firefox 7-10 (Streaming only) Internet Explorer 9.x or 10.x
Tilt Range	220° (-110° ~ +110°)	Other Players	VLC: 1.1.11 or above Quicktime: 7 or above
Preset Locations	256 preset locations	Included Accessories	
Pan/tilt/zoom Functionalities	48x digital zoom (4x on IE plug-in, 12x built-in) Auto pan mode Auto patrol mode	CD	User's manual, quick installation guide, Installation Wizard 2, ST7501 32-channel recording software
On-board Storage	SD/SDHC/SDXC card slot	Others	Wall mount bracket, screws, waterproof connectors, terminal blocks, quick installation guide, warranty card, alignment sticker, ground wire, T25 stardriver, software CD, desiccant bags
Video			
Compression	H.264, MJPEG & MPEG-4		
Maximum Frame Rate	H.264: 30 fps @ 1920x1080 60 fps @ 1280x720 MPEG-4: 30 fps @ 1920x1080 60 fps @ 1280x720 MJPEG: 30 fps @ 1920x1080 60 fps @ 1280x720 (Up to 30/60 fps in WDR mode)		
Maximum Streams	4 simultaneous streams		
S/N Ratio	Above 50 dB		
Dynamic Range	Above 86 dB		
Video Streaming	Adjustable resolution, quality and bitrate Zoom enhancement for better image quality under limited bandwidth		
Image Settings	Adjustable image size, quality and bit rate Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks (Up to 24) Scheduled profile settings Defog		
Audio			
Audio Capability	Audio input/output (full duplex)		
Compression	AAC, G.711, G.726		
Interface	External microphone input External line output		
Network			
Users	Live viewing for up to 10 clients		
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X		
Interface	10Base-T/100 BaseTX Ethernet (RJ-45)		
ONVIF	Supported, specification available at www.onvif.org		

Dimensions



Compatible Accessories

Mounting Kits

	AM-116 20 cm pendant pipe		AM-231 Parapet mounting kit		AM-519 1.5" PT adapter
	AM-117 40 cm pendant pipe		AM-221 Goose neck mounting kit		
	AM-118 Indoor pendant head		AM-103 Recessed kit		

PoE Kits

	AP3001 PoE plus injector		AP-331 High power PoE injector		AA-341 AC 24V power adapter
--	------------------------------------	--	--	--	---------------------------------------

Others

	AC-212 Smoked cover		AC-111 Vandal-proof transparent cover		AO-001 Combo cable
--	-------------------------------	--	---	--	------------------------------

All specifications are subject to change without notice. Copyright © VIVOTEK INC. All rights reserved.

Distributed by:



VIVOTEK INC.
6F, No.192, Lien-Cheng Rd., Chung-Ho,

VIVOTEK USA
2050 Ringwood Avenue,

VIVOTEK Europe
Randstad 22-133, 1316BW Almere,

Ver 1.3

