

B6220 | Bullet

2MP Varifocal Outdoor IR Camera

www.zavio.com

ZAVIO
Innovating IP since 2006



- | | | |
|---------------------------------|---|-------------------------------|
| • 1/2.8" 2MP CMOS sensor | • 40m IR range | • Two way audio (full duplex) |
| • Varifocal lens 2.8-12mm, F1.6 | • ROI (Region Of Interest) | • 2 alarm in / 1 alarm out |
| • 1080p @ 30fps | • Corridor mode | • 12V DC & PoE (802.3af) |
| • D-WDR | • Operating conditions -30~ 60°C | • IP66 |
| • 3D DNR | • Micro SD/SDHC/SDXC card slot up to 32GB | • ONVIF 2.4 & Profile S |

ZAVIO B6220 outdoor bullet is a compact and affordable camera - with 1080p resolution, H.264 compression, IR LEDs, PoE and IP66 weatherproof, fits the bill for most applications where a clear image day and night is all that's needed.

Featuring ROI (Region of Interest) and Corridor mode, allows you to spend your precious bandwidth and storage on the areas that really matter and helping you to make the most of your field of view by changing the standard landscape mode into corridor mode for staircases, aisles, tunnels and many more.

B6220 can be used in all kinds of applications, outdoors and indoors. Compatible with ZAVIO CamGraba 2.0, the most professional free NVR software that can support up to 64 IP cameras.

Optional accessories

Accessory: Junction box
Item number: AZ-M01
Dimensions: 119 x 39mm
Compatible with: B6220, B6330, B6530, B6210, B6320, B6520, D6210, D6320, D6520

Junction box



B6220 with junction box



Features

ROI (Region of Interest)

Defining a Region Of Interest will allow you to spending less bandwidth in areas that are less important, while relocating resolution on the most relevant part.



High Performance IR

With just 2 high performance IR LEDs, the camera is able to achieve IR range of up to 40meters distance without flashlight effect.

Easy Focus

Onboard focus adjustment buttons for easy onsite installation. Extremely easy to adjust, just untight screws, focus, tightent screws back - done!



Technical Specifications

Camera

Camera Type	2MP Varifocal Outdoor IR Bullet
Image sensor	1/2.8" CMOS sensor
Lens	Varifocal 2.8-12 mm, F1.6
Horizontal view angle	105° - 35°
IR working distance	40m effective range
Min illumination	0.01 lux @ F1.6 (color) 0.001 lux @ F1.6 (B/W)
WDR	D-WDR
Day/Night function	Mechanical IR cut filter, Light sensor

Video & Audio

Resolutions	Motion JPEG/H.264: 2 Profile from 1920 x 1080 to 320 x 240 (total 5 resolutions) 2 Profile from 640 x 480 to 320 x 240 (total 3 resolutions)
Video compression	Motion JPEG H.264 baseline/ main profile/high profile -
Frame rate	H.264: up to 30 fps at 1920 x 1080 Motion JPEG : up to 30 fps at 1920 x 1080
Video streaming	Simultaneous Motion JPEG, H.264 Controllable frame rate and bandwidth Support unicast (Real Time Streaming Protocol)
Image settings	Rotation: mirror, flip, mirror flip, corridor mode Brightness, contrast, saturation, sharpness Overlay capabilities: time, date, text and privacy Image ROI 3D DNR -
Audio support	Two-way (full duplex)
Audio compression	G.711 u law, a law, G.726, AMR

I/O & Connector

Ethernet	RJ-45 Ethernet 10/100 Base -T
Power Supply	DC Jack, 12V DC, 1A Power consumption: Max 10.5W PoE(Power over Ethernet) built-in IEEE 802.3af
Alarm I/O	Terminal block, 2/1
Audio connector	RCA, line in & line out
Analog video output	-
RS-485	-
Edge storage	Micro SD/SDHC/SDXC up to 32GB
Buttons	Reset push button
Other(s)	-

Alarm & Event

Input	Alarm buffer, alarm input, motion detection, audio detection, periodical, network link down.
Output	Network storage, edge storage, FTP, SMTP, HTTP event, HTTPS, alarm out pre and post event image.

Network

Users	5 simultaneous users
Security	Multiple user access levels with password protection, HTTPS encryption
Supported protocols	IPv4, IPv6, Bonjour, TCP/ IP, DHCP, DNS, DynDNS, PPPoE, ARP, ICMP, FTP, SMTP, NTP, UPnP, RTSP, RTP, RTCP, HTTP, HTTPS, SSL, TCP, UDP
ONVIF	2.4 & Profile S

General

Housing	Aluminum Alloy
Ingress Protection	IP66 rated weatherproof housing
Impact Protection	-
Other(s)	-
Operating conditions	Starting temperature: -10 ~ 60°C Humidity 10-100% RH Working temperature: -30 ~ 60°C Humidity 10-100% RH
Dimensions(HxWxD)	φ96 x 263mm, incl. bracket
Weight	750g excl. power supply
Included accessories	Quick installation guide, mounting and connector kit.
Optional accessories	Junction box
Certification	CE, FCC, RoHS
Language	Chinese, Croatian, Czech, Danish, Dutch, English, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Slovak, Spanish, Swedish, Turkish

System Requirements

Operating system	Windows XP / 7 / 8 / 8.1, MAC OS, Linux
Browser	Internet Explorer 9 / 10 / 11, Chrome, Firefox, Safari

Software

Video management software	ZAVIO CamGraba 2.0 IP System software, for viewing, recording and archiving up to 64 cameras.
Installation, management and maintenance	ZAVIO Installation Tool makes camera management easier with camera image preview, firmware upgrade of multiple cameras, reset cameras to default while keeping network settings, etc.

